

Title (en)

SYSTEM FOR PREVENTING LIQUIDS FROM BEING DRIVEN TO THE FLAIR STACK TIP

Publication

**EP 0088776 B1 19851023 (FR)**

Application

**EP 82902735 A 19820923**

Priority

FR 8117969 A 19810923

Abstract (en)

[origin: WO8301086A1] The system according to the invention provides, in the gas flow chain, between the liquid driving source (1) and the flair or torch stack tip (5) or vent, at least one capacity, such as a vessel (6) at the foot of the flair or torch, such capacity being provided with an overflow column (10) opening under the level of the liquid, for example the sea water level, at a predetermined distance from its tapping (11) on said capacity. The invention applies particularly to sea production plants (offshore).

IPC 1-7

**E21B 41/00; E21B 43/36; F23G 7/06**

IPC 8 full level

**E21B 41/00** (2006.01); **E21B 43/36** (2006.01); **F23G 7/08** (2006.01)

CPC (source: EP US)

**E21B 41/0071** (2013.01 - EP US); **E21B 43/36** (2013.01 - EP US); **F23G 7/085** (2013.01 - EP US)

Designated contracting state (EPC)

BE DE FR GB NL SE

DOCDB simple family (publication)

**FR 2513356 A1 19830325; FR 2513356 B1 19840113;** BR 8207865 A 19830830; DE 3267050 D1 19851128; EP 0088776 A1 19830921; EP 0088776 B1 19851023; NO 831828 L 19830524; OA 08943 A 19901130; US 4547149 A 19851015; WO 8301086 A1 19830331

DOCDB simple family (application)

**FR 8117969 A 19810923;** BR 8207865 A 19820923; DE 3267050 T 19820923; EP 82902735 A 19820923; FR 8200156 W 19820923; NO 831828 A 19830524; OA 58005 A 19830523; US 50664783 A 19830523