

Title (en)

Method and device for coating internal threads of a fastener.

Title (de)

Methode und Vorrichtung zum Aufbringen eines Überzuges auf ein inneres Schraubgewinde eines Befestigungselementes.

Title (fr)

Méthode et dispositif pour appliquer un enduit sur le filetage interne d'un élément de fixation.

Publication

**EP 0090103 A1 19831005 (EN)**

Application

**EP 82301595 A 19820326**

Priority

EP 82301595 A 19820326

Abstract (en)

It includes a rotatable base (11) for holding the fastener E, and an applicator (15) having a discharge orifice (21) extending through its side wall which contacts the internal threads T at a single point of tangency, the axis of the applicator (16) being offset from the rotational axis (12) of the base (11). Thus, an induced side load force is created at the point of tangency for effecting the pressing of discharged sealant S into the roots of the threads. Differently sized internally threaded elements can be coated in accordance with the invention while using the same sealant applicator.

IPC 1-7

**B05C 7/00**; **B05C 7/06**; **B05D 7/22**

IPC 8 full level

**B05C 7/00** (2006.01); **B05C 7/06** (2006.01); **B05D 7/22** (2006.01)

CPC (source: EP)

**B05C 7/00** (2013.01); **B05C 7/06** (2013.01); **B05D 7/22** (2013.01)

Citation (search report)

- [A] DE 2944056 A1 19810514 - FASTENERS LTD P S M [GB]
- [A] US 4268544 A 19810519 - WALLACE RICHARD B
- [A] FR 2201741 A5 19740426 - FISCHER AG GEORG [CH]
- [AD] US 3416492 A 19681217 - GREENLEAF RICHARD J
- [A] DE 1900343 A1 19690904 - COUSSINETS STE INDLE

Cited by

FR2757092A1; DE3433315A1; WO9826894A1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

**EP 0090103 A1 19831005**; **EP 0090103 B1 19860903**; DE 3272972 D1 19861009

DOCDB simple family (application)

**EP 82301595 A 19820326**; DE 3272972 T 19820326