

Title (en)  
Mounting for a window, a door or the like.

Title (de)  
Beschlag für ein Fenster, eine Tür od. dgl.

Title (fr)  
Ferrure pour une fenêtre, une porte ou analogues.

Publication  
**EP 0090956 A1 19831012 (DE)**

Application  
**EP 83102243 A 19830308**

Priority  
DE 3212246 A 19820402

Abstract (en)  
1. Fitting for a parallel-positionable leaf (1) of a window or of a door with at least two upper (2, 3) and two lower stays (4, 5), at least one of the lower stays (4, 5), in particular that (4) which is associated with the closing side of the leaf, being provided with a locking device (16) which is operative when the stay (4) is swung out, and wherein at least the lower stay (4) which is in the front in the closure direction (28) is articulated on a carriage (15) or slider of the leaf, characterised in that a spring loaded ratchet member (18) is displaceably mounted at least on the carriage (15) which is connected to the front lower stay (4), the or each spring loaded ratchet member (18) being constructed as a bolt adapted for longitudinal displacement in the direction of movement of the leaf (1) and in that there is disposed in the associated stay (4) a ratchet housing in the form of a notch, slot or the like to accommodate the ratchet member (18).

Abstract (de)  
Ein an wenigstens einem, vorzugsweise aber mehreren insbesondere vier Ausstellarmen (2, 3, 4, 5) gehaltener Flügel (1) läßt sich in seiner geöffneten, beispielsweise bei vier Ausstellarmen (2, 3, 4, 5) in seiner parallelabgestellten Lage, mit dem Beschlag sicher halten, so daß ihn Winddruck oder eine andere Kraft nicht in die Schließ- bzw. eine Kippstellung zurückdrücken können. Man erreicht dies dadurch, daß in der Ausstelllage an dem bzw. an wenigstens einem der nicht anderweitig sicherbaren Ausstellarme (4, 5) eine unmittelbar wirksame Sperrvorrichtung angebracht ist. Sie besteht aus einer Rastaufnahme und einem federbelasteten Rastglied. Das Ein- und Ausrasten erfolgt automatisch durch eine minimale Verschiebewegung des Flügels (1) gegenüber seinem Blendrahmen (6) od. dgl. Zu diesem Zweck wirkt ein Auflaufelement (31) am Blendrahmen (6) mit einem Auslöser am Flügel (1) bzw. an dessen Laufwagen (5) sowie mit einer Pelastungsfeder zusammen.

IPC 1-7  
**E05D 15/56**; **E05D 15/10**

IPC 8 full level  
**E05D 15/10** (2006.01); **E05D 15/56** (2006.01)

CPC (source: EP)  
**E05D 15/1015** (2013.01); **E05D 2015/1031** (2013.01); **E05Y 2900/148** (2013.01)

Citation (search report)  
• [X] DE 2648344 B2 19810903  
• [X] DE 2218678 A1 19731025 - GROEZINGER KG  
• [X] DE 7037617 U 19720525  
• [A] DE 2839797 A1 19800306 - KOLLER METALLBAU AG

Cited by  
EP2672045A3; DK201470766A1; EP0231498A3; EP0270748A3; US4845891A; EP0103725B1

Designated contracting state (EPC)  
AT BE CH FR GB LI NL

DOCDB simple family (publication)  
**EP 0090956 A1 19831012**; **EP 0090956 B1 19860723**; **EP 0090956 B2 19890913**; AT E20942 T1 19860815; DE 3212246 A1 19831013; DE 3212246 C2 19850905

DOCDB simple family (application)  
**EP 83102243 A 19830308**; AT 83102243 T 19830308; DE 3212246 A 19820402