

Title (en)
INDIRECT ELECTROSTATIC PRINTER

Publication
EP 0091074 B1 19860924 (FR)

Application
EP 83103118 A 19830329

Priority
FR 8205726 A 19820402

Abstract (en)
[origin: US4514078A] An indirect electrostatic printer is characterized in that the intermediate medium in the form of a dielectric tape (1) is mounted in an open loop defined by a supply reel (2), an auxiliary roller (4) over which its path doubles back and a take up reel (3), and in that said auxiliary roller (4) and an associated pressure roller (14) define a combined station (7) for simultaneously transferring and fixing the image on the final medium which is in the form of individual sheets (8), and said auxiliary roller and said pressure roller constituting, together with said tape (1), means for conveying the sheets to a copy delivery station (15).

IPC 1-7
B41J 3/18

IPC 8 full level
B41J 2/41 (2006.01); **G03G 15/22** (2006.01); **G03G 15/28** (2006.01); **G03G 15/32** (2006.01)

CPC (source: EP US)
G03G 15/283 (2013.01 - EP US); **G03G 15/321** (2013.01 - EP US)

Cited by
EP0359571A3; EP0240938A3; FR2608098A1; EP0222224A1; FR2589104A1; US4723137A

Designated contracting state (EPC)
BE DE FR GB IT LU NL SE

DOCDB simple family (publication)
EP 0091074 A1 19831012; EP 0091074 B1 19860924; CA 1191188 A 19850730; DE 3366381 D1 19861030; FR 2524390 A1 19831007; FR 2524390 B1 19861017; IE 54161 B1 19890705; IE 830741 L 19831002; JP H0257781 B2 19901205; JP S58187380 A 19831101; US 4514078 A 19850430

DOCDB simple family (application)
EP 83103118 A 19830329; CA 425045 A 19830331; DE 3366381 T 19830329; FR 8205726 A 19820402; IE 74183 A 19830331; JP 5773583 A 19830401; US 48208483 A 19830404