

Title (en)

ELECTROPHOTOGRAPHIC COPYING PROCESS AND APPARATUS FOR REMOVING THE DEVELOPER LIQUID FROM A PHOTOCONDUCTOR SURFACE

Publication

**EP 0092107 B1 19860611 (DE)**

Application

**EP 83103347 A 19830406**

Priority

DE 3213797 A 19820415

Abstract (en)

[origin: US4482242A] In the method and apparatus of the present invention, a voltage of up to 1,800 V is applied to the photoconductor surface of the drum of an electrophotographic copier. A latent charge image is formed by exposing the photoconductor surface and the latent charge image is developed by contact with a developing liquid to form a toner image. Excess developer is removed by a stripping roller which contacts the drum and rotates at a speed which is up to 20% faster than that of the drum.

IPC 1-7

**G03G 15/10**

IPC 8 full level

**G03G 21/10** (2006.01); **G03G 13/26** (2006.01); **G03G 15/10** (2006.01); **G03G 15/11** (2006.01)

CPC (source: EP US)

**G03G 15/11** (2013.01 - EP US)

Cited by

US6029035A; EP1008916A4

Designated contracting state (EPC)

BE DE FR GB IT NL

DOCDB simple family (publication)

**EP 0092107 A1 19831026**; **EP 0092107 B1 19860611**; AU 1324383 A 19831020; AU 551303 B2 19860424; CA 1205126 A 19860527; DE 3213797 A1 19831020; DE 3364049 D1 19860717; JP S58187980 A 19831102; US 4482242 A 19841113

DOCDB simple family (application)

**EP 83103347 A 19830406**; AU 1324383 A 19830408; CA 424999 A 19830331; DE 3213797 A 19820415; DE 3364049 T 19830406; JP 6381183 A 19830413; US 48254083 A 19830406