

Title (en)

LOW-POWER HIGH-PRESSURE DISCHARGE LAMP

Publication

**EP 0092221 B1 19880720 (DE)**

Application

**EP 83103744 A 19830418**

Priority

DE 3214642 A 19820420

Abstract (en)

[origin: US4633136A] A high-pressure discharge lamp with metal halide additives and a power input of less than 100W comprises electrodes (4, 5) which have a shank portion (18) adjacent the seal and a second portion (19) which is formed as a coil and faces the discharge. Adjacent turns of the coil portion (19) do not contact one another. Shank (18) and coil (19) are preferably made of a single piece of wire. In the case of a double-ended arc tube (FIGS. 1 and 2) the axis of the coil portion (19) forms a substantially straight line with the shank portion (18). In the case of a single-ended arc tube (FIGS. 3 and 4) the axis of the coil portion includes an angle of 90 DEG with the axis of the shank portion. In order to protect the electrode, and especially the shank portion from corrosion, the shank (18) of the electrode (4, 5) is surrounded by a conical filament (17) of refractory metal e.g. tungsten whose turns are lying closely together. Due to the specific shape of the electrode (4, 5), quicker starting of the lamp is achieved, even when the lamp is still warm.

IPC 1-7

**H01J 61/073**

IPC 8 full level

**H01J 61/073** (2006.01)

CPC (source: EP US)

**H01J 61/0732** (2013.01 - EP US)

Citation (examination)

Henderson and Marsdon, Lamps and Lighting, London 1975, p. 250-256, 571

Cited by

EP0220673A3; CN105505830A

Designated contracting state (EPC)

FR GB IT

DOCDB simple family (publication)

**EP 0092221 A2 19831026; EP 0092221 A3 19840704; EP 0092221 B1 19880720; US 4633136 A 19861230**

DOCDB simple family (application)

**EP 83103744 A 19830418; US 48456883 A 19830413**