

Title (en)
METHOD OF OPENING FIBRE BALES

Publication
EP 0093235 B1 19850703 (DE)

Application
EP 83101465 A 19830216

Priority
CH 271982 A 19820504

Abstract (en)
[origin: US4566152A] The removal of flocks from the series of fiber bales is controlled by a control signal which is generated in response to a deviation from a predetermined ratio of the operating time intervals and the non-operating time intervals of the flock removal member. Flock material is continuously withdrawn from the storage receiver while delivery of flock is controlled by stop and start signals (a, e) which are produced in response to the receiver achieving maximum fill or minimum fill. A determination is made of the operating time interval between a start signal and a succeeding stop signal while a non-operating time period is determined between the stop signal and the next succeeding start signal in order to obtain the control signal.

IPC 1-7
D01G 7/00; **D01G 13/00**

IPC 8 full level
D01G 7/14 (2006.01); **D01G 7/00** (2006.01); **D01G 13/00** (2006.01)

CPC (source: EP US)
D01G 7/00 (2013.01 - EP US); **D01G 13/00** (2013.01 - EP US)

Cited by
EP0548023A1; US4928353A; GB2178873A; DE3513295A1; FR2580299A1; US4723344A; DE3513295C2

Designated contracting state (EPC)
CH DE FR GB IT LI

DOCDB simple family (publication)
EP 0093235 A1 19831109; **EP 0093235 B1 19850703**; DE 3360334 D1 19850808; JP H0321649 B2 19910325; JP S58191225 A 19831108; US 4566152 A 19860128

DOCDB simple family (application)
EP 83101465 A 19830216; DE 3360334 T 19830216; JP 6789483 A 19830419; US 48442183 A 19830412