

Title (en)

SAFETY ABUTMENT FOR THE PIVOTS OF VARIABLE POSITION STATOR VANES

Publication

**EP 0093631 B1 19860129 (FR)**

Application

**EP 83400695 A 19830406**

Priority

FR 8206117 A 19820408

Abstract (en)

[origin: US4514141A] The device consists of an arm having structure for attachment to the bottom pivot of a stator blade. Stopping elements are provided in the inner stator ring against which the arm can come to rest. The stopping elements consist of the sides of a circumferential notch formed in the inner surface of the inner ring. A C-shaped molding fastened onto the inner ring makes the notch leak-proof.

IPC 1-7

**F01D 17/16**

IPC 8 full level

**F16C 17/08** (2006.01); **F01D 17/16** (2006.01); **F01D 25/16** (2006.01); **F02C 9/22** (2006.01); **F04D 29/56** (2006.01)

CPC (source: EP US)

**F01D 17/162** (2013.01 - EP US)

Cited by

EP0146449A1; FR2556410A1; US4604030A; EP0204615A1; FR2582720A1; US4706354A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**FR 2524934 A1 19831014; FR 2524934 B1 19861226**; DE 3361967 D1 19860313; EP 0093631 A1 19831109; EP 0093631 B1 19860129; JP H029161 B2 19900228; JP S58206810 A 19831202; US 4514141 A 19850430

DOCDB simple family (application)

**FR 8206117 A 19820408**; DE 3361967 T 19830406; EP 83400695 A 19830406; JP 6149383 A 19830407; US 48294083 A 19830407