

Title (en)
Apparatus for reeling.

Title (de)
Spulvorrichtung.

Title (fr)
Dispositif de bobinage.

Publication
EP 0094784 A2 19831123 (EN)

Application
EP 83302654 A 19830511

Priority
GB 8214228 A 19820515

Abstract (en)
A continuously operable reeling machine comprises two reeling stations (1 and 2). Whilst reeling proceeds at one station (1), a full reel (B) may be removed from the other (2) and replaced by an empty reel to which the element being reeled is eventually transferred when the reel (A) at the first mentioned station (1) is full. Removal and replacement of that full reel is then undertaken whilst reeling proceeds at the other station. Each reel is supported in its reeling position by a pair of supports (4, 5). One of those supports 4 may be pivoted from its operative, reeling, position to an inoperative position which permits withdrawal and replacement of the reel in the axial direction of the reel. During withdrawal and replacement reels (A, B) are supported on trolleys (50) which may be wheeled up to and away from the reeling stations. This arrangement is simple to operate and efficient in its use of floor space.

IPC 1-7
B65H 67/04

IPC 8 full level
B65H 54/02 (2006.01); **B65H 67/052** (2006.01)

CPC (source: EP)
B65H 67/052 (2013.01)

Cited by
EP0560392A1; EP0304606A3; CN115057299A; CN113200423A; US6427937B1; WO9813287A1; WO9957052A1

Designated contracting state (EPC)
AT CH DE FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0094784 A2 19831123; **EP 0094784 A3 19850918**; DD 209165 A5 19840425; ES 522365 A0 19840416; ES 8404575 A1 19840416; FI 831674 A0 19830513; FI 831674 L 19831116; JP S58212569 A 19831210

DOCDB simple family (application)
EP 83302654 A 19830511; DD 25094783 A 19830516; ES 522365 A 19830513; FI 831674 A 19830513; JP 8425883 A 19830516