

Title (en)
Lock, especially for vehicles.

Title (de)
Schloss, insbesondere für Kraftfahrzeuge.

Title (fr)
Serrure, notamment pour véhicule automobile.

Publication
EP 0095983 A1 19831207 (FR)

Application
EP 83401087 A 19830530

Priority
FR 8209599 A 19820602

Abstract (en)
1. A latch, in particular for a motor vehicle door, of the type comprising, on one hand, a case (1) for the latch mechanism (6) and, on the other hand, a keeper (5) movable relative to this case (1), the latch mechanism being provided, on one hand, with a bolt (7B) pivotable about a pin (8) which is perpendicular to the direction of movement of the keeper (5) with which this bolt cooperates by a fork-shaped portion (24), and, on the other hand, with a movable lever (9) for actuating the latch which is adapted to allow the rotation of the bolt (7B) in the direction for releasing the keeper (5) through a locking element (12) interposed between the bolt and the actuating lever, the locking element (12) being mounted to be movable, in one one the two parts formed by the bolt and the actuating lever between a projecting position for inter-connecting the parts and a retracted position for allowing the free movement of rotation of the bolt relative to the lever, the second of the two parts comprising for the interconnection at least one notch (30) in which the locking element (12) is adapted to penetrate, the two parts (7B, 9) being mounted in such manner as to be capable of moving away from each other so as to shift the locking element (12) out of the notch (30) provided in said second part, characterized in that the bolt (7B) is coupled to an assisted mechanism (33, 81) for driving it around its pivot pin (8) in the direction for locking the latch.

Abstract (fr)
Dans cette serrure, le pêne (7B) peut être pivoté dans le sens du blocage de la serrure, par un mécanisme d'entraînement assisté comportant un moteur électrique (33) et un équipement mobile (81) qui comporte notamment un secteur denté (82) coopérant avec le pêne (7B) par l'intermédiaire de dentures conjuguées (83, 84). Un détecteur (92, 94) déclenche la rotation du moteur dès que le pêne (7B) commence à se déplacer à partir de sa position d'ouverture, en début de phase de fermeture de la serrure.

IPC 1-7
E05B 47/00

IPC 8 full level
E05B 65/12 (2006.01)

CPC (source: EP)
E05B 81/20 (2013.01); **E05B 81/36** (2013.01); **E05B 81/54** (2013.01); **E05B 81/06** (2013.01); **E05B 81/90** (2013.01)

Citation (search report)
• [A] FR 2472651 A1 19810703 - CERDAN JACQUES [FR]
• [A] US 3332713 A 19670725 - DE CLAIRE JAMES H, et al

Cited by
US4569544A; EP0153231A1; FR2559535A1; US2020263458A1; US11834870B2; CN110469195A; FR2606450A1; US2023228322A1

Designated contracting state (EPC)
DE GB IT SE

DOCDB simple family (publication)
EP 0095983 A1 19831207; **EP 0095983 B1 19850904**; DE 3360721 D1 19851010; ES 289444 U 19860401; ES 289444 Y 19861201; FR 2528097 A2 19831209; FR 2528097 B2 19841221

DOCDB simple family (application)
EP 83401087 A 19830530; DE 3360721 T 19830530; ES 289444 U 19830601; FR 8209599 A 19820602