

Title (en)

ARRANGEMENT FOR THE PRODUCTION OF LONGITUDINAL SCREED SLABS CONSISTING OF CONCRETE

Publication

**EP 0096036 B1 19860625 (EN)**

Application

**EP 82902103 A 19820709**

Priority

SE 8104292 A 19810710

Abstract (en)

[origin: WO8300177A1] Arrangement for ensuring in connection with the production of concrete screed beams for concrete floors or similar devices good linearity of the product when casting in accordance with the so-called battery method. On a bed of beams (1) pipes (2) with a certain degree of levelling (3) are placed. In the mould the beams (1) become the underside whereas two nearby pipes (2) become the side walls. The arrangement consists in a plate (5) between two beams (1). The plate is located and shaped in such a way that the T-shaped rail (4) at the bottom of the pipe fits into a recess (6) in the plate. In this way the pipes are aligned, which is the necessary condition for ensuring good linearity of the product.

IPC 1-7

**E04G 21/10**

IPC 8 full level

**E04G 21/10** (2006.01); **B28B 7/24** (2006.01)

CPC (source: EP)

**B28B 7/246** (2013.01)

Designated contracting state (EPC)

AT CH DE FR GB LI LU NL

DOCDB simple family (publication)

**WO 8300177 A1 19830120**; DE 3271832 D1 19860731; DK 100883 A 19830228; DK 100883 D0 19830228; DK 152793 B 19880516; DK 152793 C 19881010; EP 0096036 A1 19831221; EP 0096036 B1 19860625; FI 72371 B 19870130; FI 72371 C 19870511; FI 832860 A0 19830809; FI 832860 A 19830809; JP S58501081 A 19830707; SE 447004 B 19861020; SE 8104292 L 19830111

DOCDB simple family (application)

**SE 8200240 W 19820709**; DE 3271832 T 19820709; DK 100883 A 19830228; EP 82902103 A 19820709; FI 832860 A 19830809; JP 50214582 A 19820709; SE 8104292 A 19810710