

Title (en)

A FLUID JET PRINT HEAD, AND A METHOD OF STIMULATING THE BREAK UP OF A FLUID STREAM EMANATING THEREFROM

Publication

**EP 0097413 B1 19860618 (EN)**

Application

**EP 83301874 A 19830331**

Priority

US 39010582 A 19820621

Abstract (en)

[origin: EP0097413A1] A fluid jet print head includes an elongated body (10) having a length substantially greater than its other dimensions and defining a fluid receiving reservoir (16) in one end. An orifice plate (12) is secured to the body (10) over the reservoir (16), and includes a row of orifices (18) from which fluid, supplied under pressure to the reservoir, emerges as a fluid filament. The print head includes a support (34) for engaging the body (10) intermediate its ends. Further, the print head includes a pair of piezoelectric transducers (36), bonded to the exterior of the print head body on opposite sides thereof, for alternately elongating and contracting in phase in the direction of elongation of the print head body. This causes mechanical vibration of the body and break up of the fluid filament into drops. Alternately, the piezoelectric transducers may be driven out of phase such that the print head body flexes.

IPC 1-7

**B41J 3/04**

IPC 8 full level

**B41J 2/02** (2006.01); **B41J 2/025** (2006.01); **B41J 2/12** (2006.01)

CPC (source: EP)

**B41J 2/025** (2013.01); **B41J 2/03** (2013.01); **B41J 2/105** (2013.01); **B41J 2/185** (2013.01)

Cited by

US4646104A; EP0639458A3; US5407136A; EP0588618A3; US6336708B1

Designated contracting state (EPC)

BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0097413 A1 19840104**; **EP 0097413 B1 19860618**; CA 1219776 A 19870331; DE 3364155 D1 19860724; JP H038946 B2 19910207; JP S595071 A 19840111

DOCDB simple family (application)

**EP 83301874 A 19830331**; CA 425460 A 19830408; DE 3364155 T 19830331; JP 10484083 A 19830611