

Title (en)
METHOD AND APPARATUS FOR SEPARATING A SUSPENSION BAR FROM AN ELECTRODE

Publication
EP 0097679 B1 19860305 (FR)

Application
EP 83900174 A 19821222

Priority
LU 83857 A 19811224

Abstract (en)
[origin: WO8302289A1] Method and apparatus for separating a suspension bar (14) from an electrode (11) which is vertically suspended from said bar and which comprises, in addition to that bar, an electrolytic plate (12) and one or a plurality of suspension loops (13) secured to the plate, the suspension bar traversing said loops. The suspension bar (14) is first released from the weight of the plate (12) by bringing the electrode (11) in a horizontal position wherein the plate (12) of the electrode may rest on a support (34 or 34'). The position of the bar (14) is then changed with respect to the position of the plate (12) by moving the support (34 or 34') with the plate (12) in a direction parallel to the longitudinal axis of the bar (14) while retaining the latter.

IPC 1-7
C25C 7/06

IPC 8 full level
B65H 29/54 (2006.01); **C25C 7/02** (2006.01); **C25C 7/06** (2006.01)

CPC (source: EP US)
C25C 7/06 (2013.01 - EP US); **Y10T 29/49117** (2015.01 - EP US); **Y10T 29/53274** (2015.01 - EP US)

Cited by
DE4414271A1; DE4414271B4; DE4414271B8

Designated contracting state (EPC)
BE DE GB SE

DOCDB simple family (publication)
WO 8302289 A1 19830707; DE 3269767 D1 19860410; EP 0097679 A1 19840111; EP 0097679 B1 19860305; JP S58502153 A 19831215; LU 83857 A1 19830902; US 4577401 A 19860325

DOCDB simple family (application)
BE 8200025 W 19821222; DE 3269767 T 19821222; EP 83900174 A 19821222; JP 50025983 A 19821222; LU 83857 A 19811224; US 52020983 A 19830804