

Title (en)

TRANSFER SHEETS FOR THE THERMAL DRY-PRINTING OF CELLULOSIC FIBRES

Publication

EP 0099333 B1 19860924 (DE)

Application

EP 83810295 A 19830630

Priority

CH 422582 A 19820712

Abstract (en)

[origin: WO8400325A1] The carrier surface is used for dry thermal printing by means of colorants which are not water soluble at a temperature of 60<o>C, of water-swollen cellulose fibers. The colorants are hardly vaporizable and may not be transferred in a conventional printing process. The colorants are transferred to the cellulose fibers which are dewatered and stabilized by addition of polyglycol, at a temperature of 230<o>C and a pressure ranging from 10<4> to 10<6> Pa, by means of a paper sheet provided with a transfer layer. In order to increase the penetration of colorants into the textile structure, it is recommended to lower the air pressure in the transfer area down to a pressure ranging from 1 to 5 x 10<4> Pa.

IPC 1-7

B41M 5/025; **D06P 5/00**

IPC 8 full level

B41M 3/12 (2006.01); **B41M 5/025** (2006.01); **D06P 5/00** (2006.01); **D06P 5/28** (2006.01)

CPC (source: EP US)

D06P 5/005 (2013.01 - EP US); **Y10S 8/918** (2013.01 - US)

Citation (examination)

- DE 3009035 A1 19800918 - SUBLISTATIC HOLDING SA
- DE 2530885 A1 19760129 - CIBA GEIGY AG
- GB 2036091 A 19800625 - STOREY BROTHERS & CO

Cited by

EP0146504A3

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0099333 A1 19840125; **EP 0099333 B1 19860924**; AT E22418 T1 19861015; DE 3366444 D1 19861030; EP 0114833 A1 19840808; JP S59501255 A 19840719; US 4682983 A 19870728; WO 8400325 A1 19840202

DOCDB simple family (application)

EP 83810295 A 19830630; AT 83810295 T 19830630; CH 8300085 W 19830630; DE 3366444 T 19830630; EP 83901895 A 19830630; JP 50204983 A 19830630; US 84259286 A 19860312