

Title (en)
METHOD AND APPARATUS FOR THERMOMECHANICALLY ROLLING HOT STRIP PRODUCT TO A CONTROLLED MICROSTRUCTURE

Publication
EP 0099520 A3 19850731 (EN)

Application
EP 83106671 A 19830707

Priority
US 39778982 A 19820713

Abstract (en)
[origin: EP0099520A2] A hot strip mill having a final reducing stand and runout cooling means downstream of the reducing stand includes an incubator capable of coiling and decoiling the hot strip. The incubator is located intermediate the runout cooling means. In a preferred form the final reducing stand is a hot reversing mill. A second incubator and/or a temper mill and/or a slitter may be positioned downstream of the first incubator. The method of rolling includes isothermally treating the strip within a predetermined time and temperature range in the incubator prior to subsequent processing. The subsequent processing may include any one or more of the following: further deformation by cold rolling, temper rolling or cooling at a desired heat loss rate.

IPC 1-7
C21D 8/02; B21B 1/26

IPC 8 full level
B21B 39/12 (2006.01); **B21B 1/26** (2006.01); **B21B 1/32** (2006.01); **B21B 3/02** (2006.01); **B21B 37/74** (2006.01); **C21D 8/02** (2006.01); **C21D 8/08** (2006.01); **C21D 9/52** (2006.01); **G02B 21/34** (2006.01); **B21B 1/22** (2006.01); **B21B 1/34** (2006.01); **B21B 1/38** (2006.01); **B21B 45/00** (2006.01); **C21D 9/68** (2006.01)

CPC (source: EP KR US)
B21B 1/32 (2013.01 - EP US); **B21B 37/74** (2013.01 - EP US); **C21D 8/0226** (2013.01 - EP US); **C21D 8/08** (2013.01 - KR); **B21B 1/26** (2013.01 - EP US); **B21B 1/34** (2013.01 - EP US); **B21B 1/38** (2013.01 - EP US); **B21B 2001/228** (2013.01 - EP US); **B21B 2045/006** (2013.01 - EP US); **B21B 2201/04** (2013.01 - EP US); **B21B 2201/06** (2013.01 - EP US); **C21D 8/0231** (2013.01 - EP US); **C21D 8/0263** (2013.01 - EP US); **C21D 9/68** (2013.01 - EP US)

Citation (search report)
• [X] EP 0019193 B1 19840321
• [A] US 2658741 A 19531110 - JOB SCHMIDT, et al
• [A] US 3201288 A 19650817 - GRANGE RAYMOND A
• [A] US 3803891 A 19740416 - SMITH W
• [A] GB 2068281 A 19810812 - TIPPINS MACH
• [A] DE 2630877 B1 19771124 - SCHLOEMANN SIEMAG AG
• [A] DE 672122 C 19390303 - GUENTHER LOBKOWITZ
• [A] PATENT ABSTRACTS OF JAPAN, vol. 3, no. 87, 25th July 1979, page 110 C 53; & JP-A-54 065 118 (NIPPON KOKAN), 25-02-1979

Cited by
US5810951A; FR2704238A1; GB2333987A; GB2333987B; EP0301228A1; US4898629A; EP0226446A3; US4793401A; US6282938B1; US6264767B1; US6309482B1; WO9951368A1; WO9641024A1

Designated contracting state (EPC)
AT BE DE FR GB IT LU NL SE

DOCDB simple family (publication)
EP 0099520 A2 19840201; EP 0099520 A3 19850731; EP 0099520 B1 19881012; AT E37903 T1 19881015; AU 1431383 A 19840119; AU 548547 B2 19851219; BR 8302867 A 19840417; CA 1217076 A 19870127; DE 3378219 D1 19881117; ES 523187 A0 19841201; ES 534292 A0 19850701; ES 8501646 A1 19841201; ES 8506211 A1 19850701; FI 832534 A0 19830712; FI 832534 L 19840114; JP S5953625 A 19840328; JP S6366366 B2 19881220; KR 840005361 A 19841112; KR 870002184 B1 19871228; MX 162612 A 19910531; NO 831893 L 19840116; NZ 204339 A 19860910; US 4505141 A 19850319; ZA 833092 B 19840425

DOCDB simple family (application)
EP 83106671 A 19830707; AT 83106671 T 19830707; AU 1431383 A 19830506; BR 8302867 A 19830530; CA 425005 A 19830331; DE 3378219 T 19830707; ES 523187 A 19830613; ES 534292 A 19840713; FI 832534 A 19830712; JP 12563283 A 19830712; KR 830003225 A 19830713; MX 19812583 A 19830713; NO 831893 A 19830527; NZ 20433983 A 19830524; US 39778982 A 19820713; ZA 833092 A 19830502