

Title (en)

COATING IN CONFORMITY WITH A HIGH FRICTION RESISTANCE

Publication

EP 0100690 B1 19861001 (FR)

Application

EP 83401121 A 19830602

Priority

FR 8210464 A 19820615

Abstract (en)

[origin: US4608287A] A conformable sheet covering with high coefficient of friction, comprising a superficial layer made of a fine powder at least partially imbedded in a curable resin layer bonded to a lower support layer. The support layer is made of a thin sheet material having an elongation coefficient between 20 and 60% for a tensile force per linear centimeter less than 20N. There is a contact adhesive layer, protected by a pull off film, on the back side of the support layer. The new sheet covering is usable on three-dimensional surfaces.

IPC 1-7

D06N 7/00; D06N 3/00

IPC 8 full level

D06N 3/00 (2006.01); **D06N 7/00** (2006.01)

CPC (source: EP US)

D06N 3/0065 (2013.01 - EP US); **D06N 7/0055** (2013.01 - EP US); **Y10T 428/1471** (2015.01 - EP US); **Y10T 428/24405** (2015.01 - EP US);
Y10T 428/24967 (2015.01 - EP US); **Y10T 428/254** (2015.01 - EP US); **Y10T 428/266** (2015.01 - EP US); **Y10T 428/2848** (2015.01 - EP US);
Y10T 442/2344 (2015.04 - EP US)

Designated contracting state (EPC)

AT BE CH DE GB IT LI LU NL SE

DOCDB simple family (publication)

US 4608287 A 19860826; AT E22581 T1 19861015; DE 3366560 D1 19861106; EP 0100690 A1 19840215; EP 0100690 B1 19861001;
FR 2528356 A1 19831216; FR 2528356 B1 19850322

DOCDB simple family (application)

US 50190683 A 19830607; AT 83401121 T 19830602; DE 3366560 T 19830602; EP 83401121 A 19830602; FR 8210464 A 19820615