

Title (en)
LAMPHOLDER

Publication
EP 0101257 B1 19870527 (EN)

Application
EP 83304504 A 19830804

Priority
• GB 8222857 A 19820809
• GB 8223467 A 19820816
• GB 8226970 A 19820921
• GB 8235840 A 19821216
• GB 8304347 A 19830217
• GB 8306273 A 19830307
• GB 8307733 A 19830321
• GB 8312225 A 19830504

Abstract (en)

[origin: EP0101257A1] A safety lampholder in which in the absence of a bulb contacts that are accessible within the lampholder socket are electrically isolated from fixed terminals to which a supply cable is connected. The contacts are supported on a carrier and can only be moved into engagement with the fixed terminals by applying a force to a pin or pins extending into the socket. The pin may be sharp so that it cannot be pushed by an unprotected finger, or may lie along the wall of the socket so that its tip does not provide sufficient grip to an inserted finger. The pin and carrier may be relatively movable, movement of the pin relative to the carrier causing the carrier to rotate to a position in which it may move axially towards the fixed terminals.

IPC 1-7
H01R 33/96

IPC 8 full level
H01R 33/46 (2006.01); **H01R 33/96** (2006.01)

CPC (source: EP)
H01R 33/96 (2013.01); **H01R 33/962** (2013.01)

Cited by
GB2169459A; GB2226190A; GB2226190B; US7731545B1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0101257 A1 19840222; EP 0101257 B1 19870527; AU 1825483 A 19840307; AU 575536 B2 19880804; DE 3371840 D1 19870702;
JP S59501807 A 19841025; WO 8400854 A1 19840301

DOCDB simple family (application)
EP 83304504 A 19830804; AU 1825483 A 19830804; DE 3371840 T 19830804; GB 8300192 W 19830804; JP 50258783 A 19830804