

Title (en)
Filter belt press.

Title (de)
Siebbandpresse.

Title (fr)
Filtre-presse à bandes.

Publication
EP 0103565 A1 19840321 (DE)

Application
EP 83890158 A 19830912

Priority
AT 343782 A 19820914

Abstract (en)

1. A filter belt press for dewatering sludges or the like water-containing materials, in which filter belts (3, 10) are trained around dewatering drums and deflection rollers (6, 7, 8) rotatably supported on a frame (13) and in which the sludge or the like is pressed between two filter belts (3, 10), the sludge being charged onto one filter belt (3) within an approximately horizontal area between two deflection rollers and being conveyed away from the sludge charging area (2, 20) to the gap formed between both said filter belts (3, 10), said frame (13) comprising two lateral cheeks (1) being constructed of spars (5) rigidly connected with each other on which spars the bearing of the dewatering drums and of at least some of the deflection rollers (6, 7, 8) are mounted, the dewatering drums and the deflection rollers being arranged between the lateral cheeks (1), and the approximately vertical spars (5) of the lateral cheeks (1) located adjacent to the sludge charging area (2, 20) being provided with connection means for bearings (14, 15) of deflection rollers for that filter belt (3) onto which the sludge is charged, characterized in that extension pieces (16 ; 22 ; 25) projecting outwardly beyond the vertical spars (5) and located within the planes of the lateral cheeks (1) are connectable to the lateral cheeks (1) at the sludge charging side (20), said extension pieces being provided with connection means for the bearings at least of the upper deflection roller (6', 6'', 6''') and, if desired, for a deflection roller support (9', 9'', 9'''), said connection means being of similar construction as the corresponding connection means on the vertical spars (5) of the lateral cheeks (1 ; Fig. 2 ; 3 ; 4).

Abstract (de)

Die Siebbandpresse weist einen aus zwei Seitenwangen (1) bestehenden Rahmen (13) auf. Die zu entwässernden Schlämme werden auf ein Siebband (3) aufgegeben, welches über eine Umlenkrolle mit einem zweiten Siebband (10) zusammengeführt wird und gemeinsam mit diesem zweiten Siebband (10) über Entwässerungstrommeln geführt wird. Die Seitenwangen (1) weisen Anschlussstellen für über die senkrechten Holme (6) herausragende Verlängerungssteile (16) auf. An diesen Verlängerungssteilen (16) sind Anschlussstellen für die Lager von Umlenkrollen (6', 7') und Lenkketten (8') in analoger Weise wie der Rahmenholm (5) vorgesehen, so dass die Siebbandpresse wahlweise in verschiedener Lage zusammengebaut werden kann.

IPC 1-7

C02F 11/12; B01D 33/04

IPC 8 full level

B01D 33/04 (2006.01); **B01D 33/048** (2006.01); **B30B 9/24** (2006.01)

CPC (source: EP)

B30B 9/24 (2013.01)

Citation (search report)

- AT 340331 B 19771212 - ANDRITZ AG MASCHF [AT], et al
- DE 2911760 A1 19801002 - ALTMAYER
- US 2737858 A 19560313 - SIMPSON ALVAN D

Cited by

US5879551A; WO9515925A1

Designated contracting state (EPC)
CH DE FR GB IT LI NL

DOCDB simple family (publication)

EP 0103565 A1 19840321; EP 0103565 B1 19851218; AT 375059 B 19840625; AT A343782 A 19831115; DE 3361567 D1 19860130;
JP S5973200 A 19840425; JP S6054160 B2 19851128

DOCDB simple family (application)

EP 83890158 A 19830912; AT 343782 A 19820914; DE 3361567 T 19830912; JP 16907183 A 19830913