

Title (en)

CODING METHOD FOR AN ELECTRONIC KEY

Publication

EP 0103790 A3 19840905 (DE)

Application

EP 83108588 A 19830831

Priority

DE 3234538 A 19820917

Abstract (en)

[origin: EP0103790A2] In the method for coding an electronic key, a number of code numbers 1 to n are stored in the transmitter (1) and in the receiver (2). After every transmission and reception operation a new identical code number is automatically set in the transmitter (1) and receiver (2). The transmitter (1) controls via an amplifier (3) a photodiode (4) which emits a coded infrared signal (5). This signal (5) is received by a phototransistor (6) which delivers it to the receiver (2) via an amplifier (7). At the output (8) of the receiver (2) there is a signal (9), by means of which the central locking system of a motor vehicle is actuated. <IMAGE>

IPC 1-7

E05B 49/00

IPC 8 full level

G07C 9/00 (2006.01)

CPC (source: EP)

G07C 9/00182 (2013.01); **G07C 9/00309** (2013.01); **G07C 9/21** (2020.01); **G07C 2009/00253** (2013.01); **G07C 2009/00785** (2013.01); **G07C 2209/06** (2013.01)

Citation (search report)

- [A] GB 1595797 A 19810819 - PUSHMAN HUGH JOHN [GB]
- [A] WO 8202811 A1 19820819 - NELSON AVI N [US]
- [A] DE 2922230 A1 19801023 - GYGI MARTIN H
- [A] GB 1582989 A 19810121 - MOTOROLA INC
- [A] IBM TECHNICAL DISCLOSURE BULLETIN, Band 14, Nr. 12, Mai 1972, Seiten 3860-3861, Armonk, New York 10504, US G.V.A. MALMROS: "Access control system"

Cited by

EP0307749A1; FR2536781A1; EP0813170A3; US6980655B2; US10862924B2; WO2005018103A1; US11423717B2; US11869289B2; US10944559B2; US11799648B2; US10997810B2; US11462067B2; US11074773B1; US11763616B1; US12056971B1; US10652743B2; US11122430B2; US11778464B2; US12108248B2

Designated contracting state (EPC)

DE FR GB SE

DOCDB simple family (publication)

EP 0103790 A2 19840328; EP 0103790 A3 19840905; DE 3234538 A1 19840322

DOCDB simple family (application)

EP 83108588 A 19830831; DE 3234538 A 19820917