

Title (en)

ELECTRIC CONTACT PIN FOR USE IN PRINTED CIRCUIT BOARDS

Publication

EP 0105044 B1 19861029 (EN)

Application

EP 83870089 A 19830831

Priority

- BE 208920 A 19820831
- BE 210658 A 19830429

Abstract (en)

[origin: EP0105044A1] The contact pin is characterized in that the three resilient legs are symmetrically displaced upon insertion of the pin (10) in hole (15) of a printed circuit in such a manner that the outer legs (19,21) are bended towards one another so as to obtain a V-shaped configuration while the inner leg (20) acts like a wedge and is clinged between the two outer legs.

IPC 1-7

H01R 9/09

IPC 8 full level

H01R 12/58 (2011.01)

IPC 8 main group level

H01R (2006.01)

CPC (source: EP)

H01R 12/58 (2013.01)

Cited by

DE102008064590B3; DE3801352A1; EP0141492A3; FR2566969A1; AT386699B; EP0457293A1; US2012074208A1; US8701971B2; US4735587A; GB2186124A; EP0221319A1; US4698026A; US4897053A; EP0367866A1; EP0225400A1; US4775326A; US4691979A; US7377823B2; WO2006127071A1; US8317551B2

Designated contracting state (EPC)

CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0105044 A1 19840404; EP 0105044 B1 19861029; DE 3367305 D1 19861204; FI 833096 A0 19830831; FI 833096 A 19840301

DOCDB simple family (application)

EP 83870089 A 19830831; DE 3367305 T 19830831; FI 833096 A 19830831