

Title (en)

METHOD AND DEVICE FOR MOULDING A REFRACTORY LINING IN A METALLURGICAL VESSEL

Publication

EP 0105795 A3 19850821 (FR)

Application

EP 83401892 A 19830927

Priority

FR 8216388 A 19820929

Abstract (en)

[origin: EP0105795A2] This device comprises a mould (1, 2), with a shape adapted to the geometry of the vessel (C), made from several elements to permit free expansion of the mould during use, means (3, 4, 5) for supporting and handling the mould (2, 3), means (6, 14) for centring and securing the mould with respect to the vessel (C) so as to arrange, between the inner wall of the vessel (C) and the mould, a space intended to receive the refractory concrete and means (7, 8, 11) for supplying the said space with refractory concrete. <IMAGE>

IPC 1-7

B22D 41/02; **F27D 1/16**

IPC 8 full level

B22D 41/02 (2006.01); **F27D 1/16** (2006.01); **F27D 3/00** (2006.01); **F27D 23/00** (2006.01); **F27D 99/00** (2010.01)

CPC (source: EP)

B22D 41/023 (2013.01); **F27D 1/1626** (2013.01); **F27D 2003/0001** (2013.01); **F27D 2099/0008** (2013.01)

Citation (search report)

- [Y] FR 2095224 A3 19720211 - KONINKLIJKE HOOGOVENS EN STAAL [NL]
- [Y] FR 1258157 A 19610407
- [Y] US 3944193 A 19760316 - IMAI HIROYUKI, et al
- [Y] FR 2050736 A5 19710402 - COMMISSARIAT ENERGIE ATOMIQUE

Cited by

FR2732915A1; EP0716894A1; FR2728185A1; FR2646367A1; US5160692A; AU627585B2; WO9937423A1; WO9012666A1

Designated contracting state (EPC)

AT BE DE FR GB IT LU NL SE

DOCDB simple family (publication)

EP 0105795 A2 19840418; **EP 0105795 A3 19850821**; FR 2533492 A1 19840330; FR 2533492 B1 19860613

DOCDB simple family (application)

EP 83401892 A 19830927; FR 8216388 A 19820929