

Title (en)

APPARATUS FOR MAKING TORSION-CRIMPED YARNS

Publication

EP 0106067 A3 19851016 (DE)

Application

EP 83108162 A 19830818

Priority

CH 572782 A 19820929

Abstract (en)

[origin: US4553382A] The separating head of the device contains a frame (10) in which a feed bush (12) for the twisting column (11) has been inserted at the top. Underneath this bush (12) there are the first arms (28) of double-armed levers (20, 21), which levers are components of a regulating facility which also includes a damping facility (30, 31) which acts on the second arms (29) of the levers (20, 21). The threads (16, 17) kept apart by the said first arms (28) loop around conical rollers (34, 35) of an equalizing roller (32), and then pass through a hollow shaft (2) out of the separating head (1). The other end of this shaft (2), on top of which the separating head sits tight, can be driven by means of a motor (7) via toothed wheels (5, 6).

IPC 1-7

D02G 1/02

IPC 8 full level

B21F 35/00 (2006.01); **D02G 1/02** (2006.01)

CPC (source: EP US)

D02G 1/028 (2013.01 - EP US)

Citation (search report)

- [Y] DE 1660210 A1 19700716 - ZINSER TEXTILMASCHINEN GMBH
- [Y] US 3327462 A 19670627 - KIRK WYATT WILLIAM
- [A] US 3747317 A 19730724 - WILLIS T
- [A] DE 1435477 A1 19681121 - HEBERLEIN & CO AG
- [A] CH 418515 A 19660815 - HEBERLEIN & CO AG [CH]
- [A] GB 784004 A 19571002 - FINE SPINNERS & DOUBLERS LTD

Cited by

DE19546372C1; FR2742169A1; WO2005087987A3

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0106067 A2 19840425; EP 0106067 A3 19851016; JP S5982130 A 19840512; US 4553382 A 19851119

DOCDB simple family (application)

EP 83108162 A 19830818; JP 18009783 A 19830928; US 53298683 A 19830916