

Title (en)

DEVICE FOR PROJECTING DROPLETS OF AN ELECTRICALLY CONDUCTIVE LIQUID

Publication

EP 0106802 B1 19870225 (FR)

Application

EP 83810452 A 19831005

Priority

CH 591482 A 19821008

Abstract (en)

[origin: WO8401544A1] The device comprises an electrode (2) of which the diameter is of the same magnitude order as the droplet to be projected, said electrode emerging at the surface of an electrically insulating support (1). Said support (1) is immersed into a liquid reservoir (3) presenting an opening (4). The support (1) is arranged so that its face wherein the electrode (2) is flush is recessed by a certain distance from the plane of the opening (4) so that said face is covered by the liquid contained in the reservoir (3) wherein a counter electrode (5) is arranged. Those electrodes (2, 5) are connected to an intermittent current source intended to form an electric field through the liquid which, by concentration to the portion of the electrode (2) emerging from the support (1) causes the projection of a liquid droplet.

IPC 1-7

B41J 3/04

IPC 8 full level

B41J 2/015 (2006.01); **B41J 2/045** (2006.01); **B41J 2/055** (2006.01); **B41J 2/06** (2006.01)

CPC (source: EP US)

B41J 2/06 (2013.01 - EP US); **B41J 2002/061** (2013.01 - EP US); **B41J 2202/04** (2013.01 - EP US)

Citation (examination)

EP 0046295 A1 19820224 - MATSUSHITA ELECTRIC IND CO LTD [JP]

Cited by

EP0418659A3; EP0694390A3; EP0363325A1; US5001496A; CH677755A5; US6315395B1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0106802 A1 19840425; EP 0106802 B1 19870225; AT E25506 T1 19870315; CH 649040 A5 19850430; DE 3369837 D1 19870402; JP H0521744 B2 19930325; JP S60500010 A 19850110; US 4575737 A 19860311; WO 8401544 A1 19840426

DOCDB simple family (application)

EP 83810452 A 19831005; AT 83810452 T 19831005; CH 591482 A 19821008; CH 8300110 W 19831005; DE 3369837 T 19831005; JP 50308683 A 19831005; US 61955784 A 19840607