

Title (en)

CONTACT DISCONNECTING DEVICE WITH BRIDGING CONTACT BLADES FOR PULL-OUT SWITCH-GEAR

Publication

EP 0107611 B1 19860820 (DE)

Application

EP 83730087 A 19830920

Priority

DE 3236495 A 19820930

Abstract (en)

[origin: US4486636A] A break contact arrangement is disclosed. One piece spacers provided with angled-off arms determine the mutual spacing of contact segments and guide the contact segments within a holder comprising side walls and sheet metal covers. The contact segments are spaced by the arms of the spacers. Each spacer includes a U-shaped central portion which is received in a recess of the contact segments and extensions at opposite ends which are fastened to the side walls of the holder. The contact forces are supplied by one-piece springs which have spring arms for each contact segment. The break contact arrangement is particularly well suited for pullout-type low-voltage and medium-voltage switchgear for connecting conductors of rectangular cross section.

IPC 1-7

H01H 1/42

IPC 8 full level

H01H 1/38 (2006.01); **H01H 1/42** (2006.01); **H02B 11/04** (2006.01)

CPC (source: EP US)

H01H 1/42 (2013.01 - EP US)

Cited by

EP2164136A3; EP0702427A3; EP0451531A1; US5098318A; DE4405900A1; US5807145A; DE102020211508A1; EP1026801A2; WO9522830A1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0107611 A1 19840502; EP 0107611 B1 19860820; DE 3236495 A1 19840405; DE 3236495 C2 19870527; DE 3365461 D1 19860925; IN 160922 B 19870815; JP S5983510 A 19840515; JP S6358004 B2 19881114; MX 154016 A 19870323; US 4486636 A 19841204

DOCDB simple family (application)

EP 83730087 A 19830920; DE 3236495 A 19820930; DE 3365461 T 19830920; IN 1136CA1983 A 19830916; JP 18176983 A 19830929; MX 19888883 A 19830928; US 53373683 A 19830919