

Title (en)

Electrohydraulic drive for process line winders, unwinders and other equipment.

Title (de)

Elektrohydraulischer Antrieb für Wickel- und Abwickelvorrichtungen und andere Einrichtungen in Fertigungsstrassen.

Title (fr)

Entraînement électro-hydraulique pour bobinoirs, dérouleurs et autres arrangements équipant des chaînes de production.

Publication

**EP 0107959 A2 19840509 (EN)**

Application

**EP 83306411 A 19831021**

Priority

US 43597582 A 19821022

Abstract (en)

An electrohydraulic drive for process line equipment, especially a spooler that winds and pays out an indefinite length of metallic strand, varies the output torque of a hydraulic motor by controlling its displacement and the pressure differential between its inlet and outlet. A valve controlled by a proportional actuator reduces the supply pressure of the hydraulic fluid in a feed line for the motor. A sequence valve located in a return line from the motor maintains the pressure at the motor outlet at a preselected and adjustable value. During braking, fluid from the return line is directed to a regeneration circuit that includes a flow divider. A portion of the flow is returned to the feed line to conserve the fluid flow. Another portion is returned to a supply reservoir for cooling. A servo-amplifier circuit includes an integrating amplifier that compares the actual rotation speed of the motor to a speed command signal. An analog multiplier produces a control signal for the proportional actuator that is the scale product of the output signal of the "speed" amplifier and a pressure limit signal. In the preferred form a tensiometer monitors strand tension and produces an input signal to a computer that modifies the pressure limit signals. The computer interfaces with other input and output devices and also controls the speed command and displacement of the motor. A hydraulic cylinder controls the linear traversing movement of the spooler under the control of a high speed servo valve that in turn is controlled by electronic circuitry. Position, velocity and rotation speed transducers for the spooler and a position transducer for the strand provide input signals to the circuitry.

IPC 1-7

**B21C 47/00; B65H 25/00**

IPC 8 full level

**B21C 47/02** (2006.01); **B65H 23/195** (2006.01); **B65H 59/38** (2006.01); **F15B 11/028** (2006.01); **G05B 11/32** (2006.01)

CPC (source: EP)

**B21C 47/02** (2013.01); **B65H 23/1955** (2013.01); **B65H 59/38** (2013.01)

Cited by

CN105508325A; BE1002897A3; EP0796807A1; FR2746380A1; DE4010352A1; CN109980993A; CN116336025A; US7380747B2

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

**EP 0188035 A2 19860723; EP 0188035 A3 19861210**; AU 2049383 A 19840503; BR 8305796 A 19840529; CA 1199704 A 19860121;  
DK 485883 A 19840423; DK 485883 D0 19831022; EP 0107959 A2 19840509; EP 0107959 A3 19840711; ES 526678 A0 19850101;  
ES 8502403 A1 19850101; FI 833436 A0 19830926; FI 833436 A 19840423; JP H0371346 B2 19911112; JP S5997971 A 19840606;  
ZA 837137 B 19840627

DOCDB simple family (application)

**EP 85202147 A 19831021**; AU 2049383 A 19831021; BR 8305796 A 19831020; CA 439172 A 19831018; DK 485883 A 19831022;  
EP 83306411 A 19831021; ES 526678 A 19831021; FI 833436 A 19830926; JP 19356183 A 19831018; ZA 837137 A 19830926