

Title (en)
Door checks.

Title (de)
Türfeststeller.

Title (fr)
Arrêt de porte.

Publication
EP 0109136 A1 19840523 (EN)

Application
EP 83301380 A 19830314

Priority
GB 8232156 A 19821110

Abstract (en)
In order to provide controlled resilient biasing of a movable check roller (12) that roller is mounted at an intermediate position on a first leg (15) of a spring bar (14), and the free end (19) of that leg is restrained to a wall (4) of a generally S-shaped bracket (1) by a pivotal engagement between a recess (20) in the bar and the wall (4). A second roller (13) is conveniently mounted on a second leg (16) of the bar. In one arrangement the second leg (16) is rigidly held against lateral movement, but in another arrangement the second leg is capable of restrained movement in a similar manner to that of the first leg.

IPC 1-7
E05C 17/20

IPC 8 full level
E05C 17/22 (2006.01); **B60J 5/04** (2006.01); **E05C 17/20** (2006.01)

CPC (source: EP KR)
E05C 17/20 (2013.01 - KR); **E05C 17/203** (2013.01 - EP)

Citation (search report)
[A] GB 795867 A 19580604 - STANDARD PRESSED STEEL CO

Cited by
US6687953B1; WO03042477A1

Designated contracting state (EPC)
AT BE CH DE FR IT LI LU NL SE

DOCDB simple family (publication)
EP 0109136 A1 19840523; EP 0109136 B1 19870114; AT E24946 T1 19870115; DE 3369171 D1 19870219; GB 2130295 A 19840531; GB 2130295 B 19860910; GB 8329914 D0 19831214; JP H0257638 B2 19901205; JP S5988579 A 19840522; KR 840006692 A 19841201; KR 890002522 B1 19890713

DOCDB simple family (application)
EP 83301380 A 19830314; AT 83301380 T 19830314; DE 3369171 T 19830314; GB 8329914 A 19831109; JP 7487083 A 19830427; KR 830001778 A 19830427