

Title (en)
ELECTRICAL OUTLET WITH PROTECTION CONTACT

Publication
EP 0109969 A3 19860702 (DE)

Application
EP 82111008 A 19821129

Priority
EP 82111008 A 19821129

Abstract (en)
[origin: EP0109969A2] 1. Electrical safety socket of a concealed, surface-mounted or (multiple) appliance design for the selective insertion of two two-pin European-type flat plugs or a conventional safety plug, wherein the pole contact bush portions (1) are disposed in the region below the insert opening in the outer cover (6) inside the base portion (3) parallel to the centrally situated safety clamp and widen-out towards each end to enclose a respective additional bush for the accommodation of flat plug pins, characterised in that, to prevent the accidental insertion of a three-pin plug at right angles to the predetermined insert facility for the safety plug or for the two European-type flat plugs, a blocking slide (5) of insulating material is provided, which slides loosely over each of the two resilient arms of the pole contact bush portions (1) and is thereby guided by the rim of the corresponding base recess (2), the blocking slide being such that it is automatically deflected by the plug pins of a safety plug or of both European-type flat plugs, but effectively eliminates the possibility of a three-pin plug being inserted if such a plug is improperly inserted transversely into one of the two pole contact bush portions (1).

IPC 1-7
H01R 27/00

IPC 8 full level
H01R 27/00 (2006.01); **H01R 13/44** (2006.01)

CPC (source: EP)
H01R 27/00 (2013.01); **H01R 13/44** (2013.01)

Citation (search report)
• [AD] DE 2915816 A1 19801106 - KOPP GMBH & CO KG HEINRICH
• [A] FR 1301448 A 19620817 - EXPL DES PROCEDES MARECHAL D
• [A] FR 2518831 A1 19830624 - OUTILLAGE MOULE ETU FABR [FR]

Cited by
FR2759207A1; EP0111756A3; EP0111757A3

Designated contracting state (EPC)
AT FR NL SE

DOCDB simple family (publication)
EP 0109969 A2 19840613; **EP 0109969 A3 19860702**; **EP 0109969 B1 19880824**; AT E36782 T1 19880915; IT 1194487 B 19880922; IT 8323922 A0 19831128

DOCDB simple family (application)
EP 82111008 A 19821129; AT 82111008 T 19821129; IT 2392283 A 19831128