

Title (en)

CIRCUIT ARRANGEMENT FOR STARTING AND OPERATING HIGH PRESSURE GAS DISCHARGE LAMPS

Publication

**EP 0111373 B1 19870527 (DE)**

Application

**EP 83201738 A 19831208**

Priority

DE 3245923 A 19821211

Abstract (en)

[origin: US4539513A] A circuit arrangement for starting and operating a high-pressure gas discharge lamp having an outer starting electrode connected to an igniter. A full-wave rectifier (1) is connected to an alternating voltage supply (A, B) and has an output shunted by a series arrangement of a diode (4) and a capacitor (5). The capacitor is discharged in part through the lamp (3) after each half period of the alternating voltage. A resistor (6), which is high-ohmic with respect to a current limiter (2), is connected in the current circuit between the end of the capacitor (5) facing the diode (4) and the lamp (3). Thus, starting of the lamp is facilitated.

IPC 1-7

**H05B 41/19**

IPC 8 full level

**H05B 41/18** (2006.01); **H05B 41/19** (2006.01); **H05B 41/282** (2006.01)

CPC (source: EP US)

**H05B 41/19** (2013.01 - EP US); **Y10S 315/07** (2013.01 - EP US)

Cited by

RU2476130C1

Designated contracting state (EPC)

AT DE FR GB NL

DOCDB simple family (publication)

**EP 0111373 A1 19840620**; **EP 0111373 B1 19870527**; AT E27528 T1 19870615; CA 1216884 A 19870120; DE 3245923 A1 19840614; DE 3371851 D1 19870702; JP S59117094 A 19840706; US 4539513 A 19850903

DOCDB simple family (application)

**EP 83201738 A 19831208**; AT 83201738 T 19831208; CA 442817 A 19831208; DE 3245923 A 19821211; DE 3371851 T 19831208; JP 23073883 A 19831208; US 55522583 A 19831125