

Title (en)
BELT TENSIONING TOOL

Publication
EP 0111831 B1 19861015 (DE)

Application
EP 83112283 A 19831207

Priority
DE 3246914 A 19821218

Abstract (en)

[origin: EP0111831A2] 1. A belt tensioning tool (23) for a belt (10), in particular pretensioned, serving for packing and/or tying purposes, which, to fix the tensioned free belt end (16), is passed through a tension jack (15) therethrough with self-locking belt looping (17), in which the tensioning tool (23) has a base member (44) with an open side wall (25) for introduction, resp. withdrawal (26) of the straight belt portion (27) passing to the tension jack (15), the base member (44) has two pivot bearings (37, 63) spaced apart in a longitudinal direction of the belt, of which the one (37) serves to support an eccentric clamp (30) adapted for actuation by a handle (42), while the other one (63) serves to support a manually swivelled (75) tensioning lever (65), deflecting means (64, 68) are provided on the tensioning lever (65) for selflocking looping (70) of the free belt end (16), and the eccentric clamp (30) has a free clamping end (60) provided with roughed areas (62), which (60) in clamped position presses the straight belt portion (27) introduced through the open side wall into the base member (44) against an abutment (28) on the base member (44), while closing the gap between the belt on the abutment (28) and its pivot bearing (37) parallel to the abutment, which are connected unilaterally by a frame arm of the base member (44), characterized in that the eccentric clamp comprises a plate-shaped clamping block (30) divided transversely into at least two plate members (31, 32), that the plate members (31, 32) of the clamping block (30) are rotatable relative to each other in the plate plane, that the abutment (28) is provided by the lower arm (29) of a C-shaped frame (24) mounted in a plane vertical to the belt extension, having a lateral opening (25), as part of the base member (44), that a tangent line (37) on the inner surface (38) of the upper C-shaped frame arm (39) provides the eccentric pivot bearing of the clamping block (30) for the abutting small face (40) of the upper plate member (31) of the clamping block (30), and that the opposite small face (60) of the lower plate member (32) of the clamping block (30) provides the free clamping end of the eccentric clamp which cooperates with the inner surface (28) of the lower C-shaped frame arm (29), and providing the abutment.

IPC 1-7
B65B 13/22

IPC 8 full level
B65B 13/02 (2006.01); **B65B 13/22** (2006.01)

CPC (source: EP)
B65B 13/025 (2013.01)

Cited by
US5059525A; EP1038776A3; US9271545B2; US9220322B2; US9332810B2; EP0867369B1

Designated contracting state (EPC)
CH DE FR GB LI

DOCDB simple family (publication)
EP 0111831 A2 19840627; EP 0111831 A3 19841114; EP 0111831 B1 19861015; DE 3246914 A1 19840620; DE 3366889 D1 19861120

DOCDB simple family (application)
EP 83112283 A 19831207; DE 3246914 A 19821218; DE 3366889 T 19831207