

Title (en)

Burner for the stoichiometric combustion of a liquid or gaseous fuel.

Title (de)

Brenner zur stöchiometrischen Verbrennung flüssiger oder gasförmiger Brennstoffe.

Title (fr)

Brûleur à combustion stoechiométrique de combustible liquide ou gazeux.

Publication

**EP 0114610 A1 19840801 (DE)**

Application

**EP 84100182 A 19840110**

Priority

DE 3301083 A 19830114

Abstract (en)

1. Burner for the stoichiometric combustion of a liquid or gaseous fuel comprising a fuel line (2) having a spray nozzle (3), an air tube (4) surrounding the fuel line which air tube is adapted to feed combustion air from a fan to the spray nozzle (3) and having a combustion tube (11) shaping the combustion chamber (12) and being connected to the air tube which combustion tube is made from a material having high temperature storing capacity, the end of which combustion tube facing the air tube (4) has an inlet opening (13) with a throttle (14) and to the opposite end of the combustion tube a cover plate (15) with a number of outlet openings (16, 16') is inserted, characterized in that the throttle (14) is shaped as a thickening (21) having in longitudinal section a triangular configuration and situated around the inner wall of the combustion tube (11) which thickening has inner wall surfaces (22, 23) each of which surrounding a truncated cone as a part of the inlet opening (13) respectively which inner wall surfaces merge in a concatenation region via a rounded region (24), and that the spray nozzle (3) is located where the throttle has its narrowest opening.

Abstract (de)

Bei einem Brenner (1) zur stöchiometrischen Verbrennung flüssiger oder gasförmiger Brennstoffe mit einer Zerstäuberdüse (3) ist an die diese umgebende Luftzuführungsleitung (4) ein die Brennkammer (12) bildendes Flammrohr (11) aus einem Werkstoff mit hoher Wärmespeicherkapazität angeschlossen, dessen dem Luftzuführungsrohr (4) zugekehrtes End eine mit einer Drossel versehene Eingangsöffnung (13) aufweist und an dessen gegenüberliegendem Ende eine mit einer Vielzahl von Austrittsöffnungen (16, 16') ausgestattete Verschlussplatte (15) vorgesehen ist. Des weiteren ist die Zerstäuberdüse (3) im Bereich des engsten Querschnittes der Drossel angeordnet.

IPC 1-7

**F23D 11/40**

IPC 8 full level

**F23D 11/40** (2006.01)

CPC (source: EP)

**F23D 11/404** (2013.01)

Citation (search report)

- US 4021191 A 19770503 - LA HAYE PAUL G
- DE 1551732 A1 19700402 - SCHWARZE ERHARD, et al
- DE 1266433 B 19680418 - OPTIMAL OELFEUERUNGSMASCHB G M
- GB 1022122 A 19660309 - SOCONY MOBIL OIL CO INC
- FR 2175480 A5 19731019 - MENDELSON RALPH [US]
- GB 934178 A 19630814 - ALFRED EDWARD MOORE
- DE 2808690 A1 19790906 - MESSERSCHMITT BOELKOW BLOHM
- DE 2810193 A1 19790913 - SWOBODA WALTER

Cited by

FR2695712A1; DE102006012168B4

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0114610 A1 19840801; EP 0114610 B1 19880330; AT E33301 T1 19880415; DE 3301083 A1 19840719; DE 3470208 D1 19880505**

DOCDB simple family (application)

**EP 84100182 A 19840110; AT 84100182 T 19840110; DE 3301083 A 19830114; DE 3470208 T 19840110**