

Title (en)

Device for cladding a door frame.

Title (de)

Einrichtung zur Verkleidung eines Türstockes.

Title (fr)

Dispositif pour le revêtement d'un châssis de porte.

Publication

EP 011554 A1 19840815 (DE)

Application

EP 83101189 A 19830208

Priority

EP 83101189 A 19830208

Abstract (en)

1. A lining for a door frame, comprising two spaced apart bars, the ends of which extend around the edge of the door frame (2, 3, 3'), wherein the ends (4a, 4a') at least partly overlap the reveal (2) and are formed with confronting open first pockets, grooves or the like (5, 5') for receiving a plate (6) for covering the reveal, and second pockets for receiving means for fastening the bars (4, 4') to the door frame, and each bar has openings (18, 18') for the fastening means (19, 19'), characterized in that those portions of the bars (4, 4') which overlap the reveal (2) are provided each with a substantially T-shaped extension (8, 10), which has a crosspiece (10), which constitutes the bottoms of the first and second pockets, the bores (18) for receiving the fastening means (19) for the bars provided at the bottom of the crosspiece (10), the openings (18) have an axis which is inclined towards the center of the door frame, the crosspiece (10) is provided with bores (11) for additional fastening means (12, 12') for holding the covering plate (6) in position relative to the bars (4, 4'), and covering or sealing bars (14' 15) for closing the second pocket are provided.

Abstract (de)

Eine Einrichtung zur Verkleidung eines Türstockes besteht aus zwei im wesentlichen U-förmigen Leisten (4, 4') aus Metall oder Kunststoff und nimmt in einander gegenüberliegenden Enden der beiden Leisten (4, 4') ausgebildeten Taschen (5, 5') eine Abdeckplatte (6) auf. Durch Verlängerung von die Taschen (5, 5') bildenden parallelen Stegen (8, 9; 8', 9') werden in den Leisten (4, 4') weitere Taschen (16, 16') festgelegt, in welchen Bohrungen (11, 18; 11') oder Öffnungen für Befestigungselemente (12, 19; 12') vorgesehen sind. Abdeckleisten (17, 14') oder Dichtungslippen verschließen die weiteren Taschen (16, 16') und verhindern damit einen Zugang zu den Befestigungselementen (12, 19, 12'), mit welchen die Leisten (4, 4') an dem Türstock befestigt sind.

IPC 1-7

E06B 1/34

IPC 8 full level

E06B 1/34 (2006.01)

CPC (source: EP)

E06B 1/347 (2013.01)

Citation (search report)

- [X] DE 7915062 U1 19790823
- [A] DE 2044043 A1 19720316
- [AD] CH 515408 A 19711115 - HOLZBAUWERK J & F HRACHOWINA F [AT]
- [A] DE 7123634 U

Cited by

DE3640691A1; GB2362412A; EP0282920A3; FR2571089A1; EP0461101A1; AT397410B

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 011554 A1 19840815; EP 011554 B1 19860604; AT E20265 T1 19860615; DE 3363859 D1 19860710

DOCDB simple family (application)

EP 83101189 A 19830208; AT 83101189 T 19830208; DE 3363859 T 19830208