

Title (en)

PACKING BETWEEN METAL FITTING AND GLASS-FIBRE ROD FOR HIGH-VOLTAGE COMPOSITE INSULATORS

Publication

**EP 0117292 B1 19901227 (DE)**

Application

**EP 83111638 A 19831122**

Priority

DE 3302788 A 19830128

Abstract (en)

[origin: US4604498A] An effective seal between the suspension mounting and the glass fiber rod of a compound high voltage insulator is obtained by filling the gap with a mixture of cross-linkable monomers or polymers formed from two or more reactive components, the mixture having a viscosity prior to cross-linking of less than 100,000 mPa.s and a penetration value between 1-500 mm/10 after cross linking. Particularly suitable are polymers based on polyorganodimethylsiloxanes.

IPC 1-7

**H01B 17/32**

IPC 8 full level

**H01B 17/32** (2006.01)

CPC (source: EP US)

**H01B 17/32** (2013.01 - EP US); **Y10T 29/49227** (2015.01 - EP US)

Designated contracting state (EPC)

DE FR GB SE

DOCDB simple family (publication)

**EP 0117292 A2 19840905; EP 0117292 A3 19871007; EP 0117292 B1 19901227**; CA 1222295 A 19870526; DE 3302788 A1 19840816; DE 3302788 C2 19871210; DE 3382095 D1 19910207; US 4604498 A 19860805; ZA 84170 B 19840829

DOCDB simple family (application)

**EP 83111638 A 19831122**; CA 446234 A 19840127; DE 3302788 A 19830128; DE 3382095 T 19831122; US 57362284 A 19840125; ZA 84170 A 19840109