

Title (en)

METHOD FOR THE DETECTION OF OPERATIVE FAILURES AND X-RAY GENERATOR FOR CARRYING OUT THIS METHOD

Publication

EP 0118160 A3 19851204 (DE)

Application

EP 84200314 A 19840306

Priority

DE 3308125 A 19830308

Abstract (en)

[origin: EP0118160A2] 1. A method of detecting operative failures in a X-ray generator, in which the desired state of operative data is compared with their measured actual state and, in the event of impermissible deviations, a value characterizing the nature of the failure is fed to a display device which in normal operation displays the preset data of the X-ray generator, characterized in that in the event of a failure the desired state and the malfunctioning actual state are additionally displayed.

IPC 1-7

H05G 1/54; H05G 1/26

IPC 8 full level

G01R 31/00 (2006.01); **G21K 1/00** (2006.01); **H05G 1/26** (2006.01); **H05G 1/54** (2006.01)

CPC (source: EP)

H05G 1/26 (2013.01); **H05G 1/54** (2013.01)

Citation (search report)

- [A] DE 2220444 A1 19731108 - KOCH & STERZEL KG
- [AD] DE 2853632 A1 19800703 - SIEMENS AG
- [A] GB 2007950 A 19790523 - FRANCE R R
- [A] DE 2510984 A1 19760930 - HOFMANN GMBH ELEKTR FRITZ
- [A] US 4035648 A 19770712 - PATEL AMBALAL T
- [A] US 3842280 A 19741015 - HERRICK N

Designated contracting state (EPC)

BE DE FR GB IT

DOCDB simple family (publication)

EP 0118160 A2 19840912; EP 0118160 A3 19851204; EP 0118160 B1 19890614; DE 3308125 A1 19840913; DE 3478736 D1 19890720;
JP S59177897 A 19841008

DOCDB simple family (application)

EP 84200314 A 19840306; DE 3308125 A 19830308; DE 3478736 T 19840306; JP 4223184 A 19840307