

Title (en)
Lasting shoes using adhesive.

Title (de)
Schuhzwicklen unter Anwendung eines Klebemittels.

Title (fr)
Montage de chaussures utilisant un adhésif.

Publication
EP 0118243 A2 19840912 (EN)

Application
EP 84300994 A 19840216

Priority
• DE 3307388 A 19830302
• US 46950383 A 19830302

Abstract (en)
In lasting shoes from the toe end at least over the ball region, adhesive is applied by an imprinter (I; 11) and nozzles (N;34), the region in which adhesive is applied by the plate extending from the toe end of the shoe and lying within, but being substantially smaller than, the region inwiped by the toe wiper assembly (W;7). The nozzles (M;34) may be guided by any suitable control, e.g. shoe-edge guidance, template (56) or programmed control. In one embodiment adhesive application takes place with the wiper assembly (W;7) in an intermediate position in which the wipers have just traversed the insole margin, such arresting of wiper assembly causing a "fall-away" signal to be supplied, in response to which the nozzles (N;34) begin their application of adhesive from adjacent the injector plate (I;11) heelwardly. When the nozzles (N;34) have moved out of the region to be wiped by the wiper assembly (W;7), the wiper assembly (W;7) is caused to continue its inwiping movement.

IPC 1-7
A43D 25/18; **A43D 25/047**; **A43D 21/16**

IPC 8 full level
A43D 21/16 (2006.01); **A43D 25/047** (2006.01); **A43D 25/18** (2006.01)

CPC (source: EP)
A43D 25/047 (2013.01); **A43D 25/185** (2013.01)

Cited by
EP1036516A1; EP1498042A1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0118243 A2 19840912; **EP 0118243 A3 19860212**; **EP 0118243 B1 19880622**; **EP 0118243 B2 19940518**; BR 8401109 A 19841016;
DE 3472206 D1 19880728

DOCDB simple family (application)
EP 84300994 A 19840216; BR 8401109 A 19840302; DE 3472206 T 19840216