

Title (en)
POTENTIOMETER

Publication
EP 0118247 B1 19870930 (EN)

Application
EP 84301032 A 19840217

Priority
GB 8304934 A 19830222

Abstract (en)
[origin: EP0118247A1] A potentiometer comprises a resistive first track (1) with first and second terminals (2, 3) to which a voltage is applied. A conductive wiper (5) traverses the first track and is connected to a third terminal (7) to provide an analogue output signal dependent on the position of the wiper. A conductive second track (8) has discrete insulating regions (9) along its length and is provided with a fourth terminal (10). The wiper (5) also traverses this second track (8). It is arranged that sharply defined transitions in electrical output (logic transitions) occur at the fourth terminal (10) as the wiper (5) traverses boundaries between the insulating regions (9) and the second track (8). The analogue output from the third terminal (7) at positions of the wiper (5) where the output transitions at the fourth terminal (10) occur, provide calibration points to permit accurate relating of the wiper position to the output from the third terminal (7) at any location between the calibration points. Particularly applicable to position sensing, e.g. in engine management systems.

IPC 1-7
H01C 10/50

IPC 8 full level
H01C 10/50 (2006.01)

CPC (source: EP)
H01C 10/50 (2013.01)

Cited by
US4706062A; DE4015415B4; FR2570177A1; AU688187B2; WO8503594A1; WO9616417A1; WO8603258A1

Designated contracting state (EPC)
DE FR GB IT SE

DOCDB simple family (publication)
EP 0118247 A1 19840912; EP 0118247 B1 19870930; DE 3466613 D1 19871105; GB 2135526 A 19840830; GB 2135526 B 19860521; GB 8304934 D0 19830323

DOCDB simple family (application)
EP 84301032 A 19840217; DE 3466613 T 19840217; GB 8304934 A 19830222