

Title (en)
CURRENT-LIMITING SWITCH

Publication
EP 0118334 B2 19920129 (FR)

Application
EP 84400205 A 19840131

Priority
FR 8301750 A 19830204

Abstract (en)
[origin: US4536630A] A current limiting switch is provided comprising two mobile levers subjected to the action of springs which apply, one against the other, separable contact pieces placed at the respective ends thereof; a thin electrically insulating screen placed between the levers so that its edge is inserted between the contact pieces while maintaining complete insulation between the levers when these latter move away from each other, following short circuit currents flowing in the switch, wherein the ends of the levers, where the contact pieces are placed, are situated in the immediate vicinity of an insulating surface of the case, so that the path of the arc is essentially tangential with respect to the movement of the mobile contacts, the movement of said edge towards and against said insulating surface causing constriction of the arc and completely insulating from one another the two opposite and sealed chambers which the screen separates within the internal volume of the case.

IPC 1-7
H01H 9/32; **H01H 77/10**

IPC 8 full level
H01H 73/38 (2006.01); **H01H 9/32** (2006.01); **H01H 77/10** (2006.01)

CPC (source: EP US)
H01H 9/32 (2013.01 - EP US); **H01H 77/108** (2013.01 - EP US); **H01H 9/446** (2013.01 - EP US)

Cited by
FR2581476A1; FR2596196A1; US4849591A; EP0185577A1; FR2573912A1; WO8705745A1

Designated contracting state (EPC)
BE CH DE GB IT LI NL SE

DOCDB simple family (publication)
EP 0118334 A1 19840912; **EP 0118334 B1 19860820**; **EP 0118334 B2 19920129**; BR 8400457 A 19840911; CA 1201468 A 19860304; DE 118334 T1 19841220; DE 3460492 D1 19860925; FR 2540666 A1 19840810; FR 2540666 B1 19861010; JP S59146127 A 19840821; US 4536630 A 19850820; ZA 84601 B 19840926

DOCDB simple family (application)
EP 84400205 A 19840131; BR 8400457 A 19840202; CA 446160 A 19840127; DE 3460492 T 19840131; DE 84400205 T 19840131; FR 8301750 A 19830204; JP 1929784 A 19840204; US 57684784 A 19840203; ZA 84601 A 19840126