

Title (en)
PROCESS AND DEVICE FOR ACTIVATING AN ELECTROMAGNETIC POSITIONER

Publication
EP 0118591 B1 19860226 (DE)

Application
EP 83107878 A 19830809

Priority
DE 3307683 A 19830304

Abstract (en)
[origin: US4544986A] A method of and an apparatus for activating an electromagnetic positioning means or actuator of the kind sometimes known as an electrical cam with relatively low currents, by alternately energizing, or energizing with currents of opposite polarity, two electromagnets to move an armature positioned therebetween between two terminal positions. The device is activated from an inactive or passive to an active state by energizing currents having at least initially a frequency greater than the resonant frequency of the positioning means. With increasing oscillations of the armature the frequency of the energizing current is reduced to zero as the device reaches its fully activated state, i.e. when the armature has oscillated in a step-like manner to one of its terminal positions. The device may be have utility for driving gas exchange valves of internal combustion engines.

IPC 1-7
F01L 9/04; **H01F 7/18**

IPC 8 full level
F01L 9/20 (2021.01); **H02K 33/12** (2006.01); **H01F 7/18** (2006.01)

CPC (source: EP US)
F01L 9/20 (2021.01 - EP US); **H01F 7/18** (2013.01 - EP US)

Cited by
DE10332489A1; EP0197357A3; EP0197356A3; EP0317725A1; DE3616540A1; US4762095A; DE19954416A1; GB2175452A; EP1099828A3; US6390113B1

Designated contracting state (EPC)
DE FR GB IT SE

DOCDB simple family (publication)
DE 3307683 C1 19840726; DE 3362302 D1 19860403; EP 0118591 A1 19840919; EP 0118591 B1 19860226; JP S59162759 A 19840913; JP S649827 B2 19890220; US 4544986 A 19851001

DOCDB simple family (application)
DE 3307683 A 19830304; DE 3362302 T 19830809; EP 83107878 A 19830809; JP 16493183 A 19830906; US 58603084 A 19840305