

Title (en)

A method for the gunning of basic gunning refractories.

Title (de)

Verfahren zum Spritzen von basischen feuerfesten Stoffen.

Title (fr)

Méthode de projection de réfractaires basiques.

Publication

**EP 0121029 A1 19841010 (EN)**

Application

**EP 83420059 A 19830330**

Priority

EP 83420059 A 19830330

Abstract (en)

A method for the gunning of a basic gunning refractory in which there is carried out a cold or hot gunning coating or filling, by a nozzle mixing method, of a gunning refractory containing a basic refractory as aggregate, not more than 5% by weight of at least one of organic fibrous materials and inorganic fibrous materials, and as binder, at least one of phosphates and silicates, characterized in that the gunning refractory is fed to the nozzle portion under air pressures in the range 1 SIMILAR 10 Kg/cm<2>, said gunning refractory is then discharged while being mixed at said nozzle portion with 5 SIMILAR 25% by weight of water having the pressure in the range 0.5 SIMILAR 5 Kg/cm2 and while being accompanied by a rotary motion, the gunning order at the start of discharging takes first air and water simultaneously and then the gunning refractory, and the distance between the nozzle end and the gunning surface is in the range 0.15 to 1.00 m while the gunning width is less than 1.00 m.

IPC 1-7

**F27D 1/16**

IPC 8 full level

**B22D 41/02** (2006.01); **F27D 1/00** (2006.01); **F27D 1/16** (2006.01)

CPC (source: EP)

**B22D 41/023** (2013.01); **F27D 1/0006** (2013.01); **F27D 1/1642** (2013.01)

Citation (search report)

- US 3229970 A 19660118 - HENRY GEORGE R
- DE 2550946 A1 19770518 - ZIOLKOWSKI H GUENTER
- FR 2231436 A1 19741227 - HOOGOSENS IJMUIDEN BV [NL]

Designated contracting state (EPC)

BE DE FR GB IT LU NL SE

DOCDB simple family (publication)

**EP 0121029 A1 19841010**; **EP 0121029 B1 19870408**; DE 3370857 D1 19870514

DOCDB simple family (application)

**EP 83420059 A 19830330**; DE 3370857 T 19830330