

Title (en)

Heat-sensitive inked element for impactless printers of thermal type.

Title (de)

Wärmeempfindliches eingefärbtes Element für anschlaglose Drucker thermischer Art.

Title (fr)

Élément encré sensible à la chaleur pour imprimantes sans impact de type thermique.

Publication

**EP 0121379 A2 19841010 (EN)**

Application

**EP 84301913 A 19840321**

Priority

IT 6735383 A 19830330

Abstract (en)

The inked element in ribbon form comprises a flexible plastics base carrier of a thickness of from 5 to 15  $\mu$  , covered with a heat-transferable coating of a thickness of 2 to 6  $\mu$  . The mixture of the coating comprises a thermoadhesive polymeric resin and a polymeric wax compatible with the resin and with the colouring pigment, in such a way as to permit printing on carriers of any type, having a Bendtsen roughness of between 10 and 500 ml/min. For improved efficient in respect of a black ribbon, added to the black is a mixture of the three complementary colours: yellow, magenta and cyan.

IPC 1-7

**B41J 3/20**

IPC 8 full level

**B41M 5/392** (2006.01); **B41J 31/00** (2006.01); **B41J 31/05** (2006.01); **B41M 5/26** (2006.01); **B41M 5/395** (2006.01); **C09D 11/00** (2006.01); **C09D 11/02** (2006.01); **C09D 11/10** (2006.01)

IPC 8 main group level

**B41J** (2006.01)

CPC (source: EP)

**B41M 5/395** (2013.01)

Cited by

DE3522801C1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 0121379 A2 19841010**; **EP 0121379 A3 19850502**; **EP 0121379 B1 19890719**; DE 3479013 D1 19890824; IT 1158916 B 19870225; IT 8367353 A0 19830330; JP S59196295 A 19841107

DOCDB simple family (application)

**EP 84301913 A 19840321**; DE 3479013 T 19840321; IT 6735383 A 19830330; JP 6504884 A 19840330