

Title (en)

HEAT-SENSITIVE INKED ELEMENT FOR IMPACTLESS PRINTERS OF THERMAL TYPE

Publication

EP 0121379 A3 19850502 (EN)

Application

EP 84301913 A 19840321

Priority

IT 6735383 A 19830330

Abstract (en)

[origin: EP0121379A2] The inked element in ribbon form comprises a flexible plastics base carrier of a thickness of from 5 to 15 mu , covered with a heat-transferable coating of a thickness of 2 to 6 mu . The mixture of the coating comprises a thermoadhesive polymeric resin and a polymeric wax compatible with the resin and with the colouring pigment, in such a way as to permit printing on carriers of any type, having a Bendtsen roughness of between 10 and 500 ml/min. For improved efficient in respect of a black ribbon, added to the black is a mixture of the three complementary colours: yellow, magenta and cyan.

IPC 1-7

B41J 3/20

IPC 8 full level

B41M 5/392 (2006.01); **B41J 31/00** (2006.01); **B41J 31/05** (2006.01); **B41M 5/26** (2006.01); **B41M 5/395** (2006.01); **C09D 11/00** (2006.01);
C09D 11/02 (2006.01); **C09D 11/10** (2006.01)

IPC 8 main group level

B41J (2006.01)

CPC (source: EP)

B41M 5/395 (2013.01)

Citation (search report)

- GB 2069160 A 19810819 - FUJI KAGAKU SHIKOGYO
- GB 2010515 A 19790627 - IBM
- EP 0076044 A2 19830406 - OLIVETTI & CO SPA [IT]
- US 3944695 A 19760316 - KOSAKA YUJIRO, et al
- EP 0033364 A1 19810812 - IBM [US]
- GB 1192920 A 19700528 - MOLINS MACHINE CO LTD [GB]

Cited by

DE3522801C1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0121379 A2 19841010; EP 0121379 A3 19850502; EP 0121379 B1 19890719; DE 3479013 D1 19890824; IT 1158916 B 19870225;
IT 8367353 A0 19830330; JP S59196295 A 19841107

DOCDB simple family (application)

EP 84301913 A 19840321; DE 3479013 T 19840321; IT 6735383 A 19830330; JP 6504884 A 19840330