

Title (en)

A TRACK MECHANISM FOR THE ORIENTATION AND DISPLACEMENT OF THE STRIPS OF A VERTICAL STRIP BLIND

Publication

EP 0122235 B1 19880720 (EN)

Application

EP 84830099 A 19840330

Priority

IT 2144583 U 19830406

Abstract (en)

[origin: EP0122235A2] The mechanism in question comprises a first spindle (2) supported by a prismatic box-like body (1), and at one end thereof it receives a toothed wheel. Fitted to the spindle (2) with the interposition of resilient biasing means, is a hollow cylindrical element (6) having a circumferential ring of projecting teeth (7). The toothed wheel (3) of the spindle (2) engages a cooperating toothed wheel (20) carried at the end of a second spindle (8) which is also formed with a support hook for one of the strips (16) of a vertical strip blind. The body (1) is housed, with the spindle (2) disposed on one side thereof, in a sliding track provided with opposed guides for the passage of a flexible control member, this latter being engageable with the toothed circumferential projection (7) formed on the hollow cylindrical element which surrounds the first spindle (1).

IPC 1-7

E06B 9/36

IPC 8 full level

E06B 9/36 (2006.01)

CPC (source: EP)

E06B 9/364 (2013.01)

Cited by

EP1342880A1; EP0323872A3; US8161295B2; WO2010135919A1; WO9109200A1

Designated contracting state (EPC)

AT BE CH DE FR GB LI NL SE

DOCDB simple family (publication)

EP 0122235 A2 19841017; EP 0122235 A3 19860319; EP 0122235 B1 19880720; AT E35842 T1 19880815; CA 1244752 A 19881115;
DE 3472816 D1 19880825; IT 8321445 V0 19830406; JP S59206586 A 19841122

DOCDB simple family (application)

EP 84830099 A 19840330; AT 84830099 T 19840330; CA 451088 A 19840402; DE 3472816 T 19840330; IT 2144583 U 19830406;
JP 6778984 A 19840406