

Title (en)
APPARATUS FOR SEALING THE EDGES OF INSULATING GLAZING UNITS

Publication
EP 0122405 B1 19860528 (DE)

Application
EP 84101832 A 19840222

Priority
DE 3310441 A 19830323

Abstract (en)
[origin: US4559001A] A glass panel whose edges are to be sealed is displaced in an upright condition standing on one edge into a sealing station where the conveyor supporting it raises somewhat whereupon suction grippers carried on a stationary frame engage within the edges of the workpiece. Then the conveyor lowers away from the workpiece, which is still upright, so that all of its edges are unobstructed. An extruder then moves vertically and horizontally around the workpiece to seal its edges. An unloading conveyor presses its own set of suction grippers against a face of the workpiece within its edges so they stick to the sealed workpiece. The suction grippers of the stationary frame then release the workpiece to those of the unloading conveyor which subsequently displaces it while it is still upright into a takeoff station.

IPC 1-7
E06B 3/66

IPC 8 full level
E06B 3/66 (2006.01); **E06B 3/673** (2006.01)

CPC (source: EP US)
E06B 3/67365 (2013.01 - EP US); **E06B 3/67347** (2013.01 - EP US); **E06B 3/67369** (2013.01 - EP US); **E06B 3/67382** (2013.01 - EP US); **E06B 2003/67378** (2013.01 - EP US)

Cited by
FR2849795A1; FR2599465A1; EP0301983A1; FR2618843A1; FR2590312A1; EP0770756A1; US5823732A; AT13586U1; US7827825B2; US11927052B2; US7988418B2; WO2004072424A1; WO2013056288A2; EP2796653A1; EP2796654A1; US10633200B2; DE202015009933U1; EP2959087B1

Designated contracting state (EPC)
AT BE CH FR GB IT LI NL

DOCDB simple family (publication)
EP 0122405 A1 19841024; EP 0122405 B1 19860528; AT E20117 T1 19860615; DE 3310441 C1 19840906; US 4559001 A 19851217

DOCDB simple family (application)
EP 84101832 A 19840222; AT 84101832 T 19840222; DE 3310441 A 19830323; US 59179184 A 19840321