

Title (en)  
IMPROVED PENDANT OR CEILING MOUNTED LUMINAIRE WITH QUICK DISCONNECT FEATURES

Publication  
**EP 0122916 B1 19870520 (EN)**

Application  
**EP 83902511 A 19830718**

Priority  
US 41232282 A 19820827

Abstract (en)  
[origin: WO8401013A1] The luminaire (10) is capable of being ceiling mounted and has a through-way electrical connection formed in a fixed housing (12) which is mounted on the ceiling or suspended from the ceiling by an attached pipe (34). The top fixed housing (12) contains a finger-safe female terminal block and a through-way means allowing building wire to be pulled straight through the housing. A pivotable housing (14) is pivotably connected to the fixed housing (12) and contains a mating male terminal block (42) which is positioned within the housing. The fixed housing and the pivotable housing may be locked together by means of a locking latch (44) so that upon release of the latch, the intermediate pivotable housing is capable of pivoting away from the fixed housing to electrically disconnect the fixture from the electrical circuit. The new and novel luminaire may be fused as desired adjacent to one or two of the male terminal connections.

IPC 1-7  
**F21V 23/06**; **F21V 21/02**

IPC 8 full level  
**F21V 21/02** (2006.01); **F21V 23/06** (2006.01)

CPC (source: EP)  
**F21V 21/02** (2013.01); **F21V 23/06** (2013.01)

Cited by  
DE3806914A1; DE3806914C2

Designated contracting state (EPC)  
BE DE FR GB NL SE

DOCDB simple family (publication)  
**WO 8401013 A1 19840315**; CA 1222496 A 19870602; DE 3371684 D1 19870625; EP 0122916 A1 19841031; EP 0122916 B1 19870520; ES 525179 A0 19850201; ES 8503106 A1 19850201; SG 108787 G 19880520; ZA 836184 B 19841031

DOCDB simple family (application)  
**US 8301102 W 19830718**; CA 433714 A 19830802; DE 3371684 T 19830718; EP 83902511 A 19830718; ES 525179 A 19830826; SG 108787 A 19871217; ZA 836184 A 19830822