

Title (en)

WORK FEEDING DEVICE AND METHOD FOR A SEWING MACHINE

Publication

EP 0123036 B1 19860903 (DE)

Application

EP 84101559 A 19840215

Priority

CH 157483 A 19830323

Abstract (en)

[origin: US4567838A] The lifting device (19) of the presser foot (21) of a sewing machine is operable through the use of an operating axle (18) and a toggle lever (20). The operating axle (18) is connected to a slide (15) capable of engaging and disengaging a coupling mechanism (10). The coupling mechanism (10) is arranged between the lifting device (6) of the feed dog (3) and the oscillating drive means (7) of the lifting device. During the lifting of the presser foot (21) by means of the toggle lever (20), the coupling pin (12) of the coupling mechanism (10) is simultaneously placed out of engagement with the driven oscillating lever (8) by means of the slide (15). Thus the drive of the lifting device (6) is interrupted, and a spring (13) pulls the feed dog (3) into its lowered position. Thus the manipulation of the sewing material is made possible without the feed dog presenting an obstacle.

IPC 1-7

D05B 27/24

IPC 8 full level

D05B 27/24 (2006.01)

CPC (source: EP US)

D05B 27/24 (2013.01 - EP US)

Designated contracting state (EPC)

DE FR GB IT SE

DOCDB simple family (publication)

EP 0123036 A1 19841031; EP 0123036 B1 19860903; AU 2602584 A 19840927; AU 558206 B2 19870122; CH 658268 A5 19861031;
DE 3460585 D1 19861009; JP S59174188 A 19841002; JP S6234536 Y2 19870903; JP S6276977 U 19870516; US 4567838 A 19860204

DOCDB simple family (application)

EP 84101559 A 19840215; AU 2602584 A 19840322; CH 157483 A 19830323; DE 3460585 T 19840215; JP 15956986 U 19861020;
JP 4303984 A 19840308; US 58685984 A 19840306