

Title (en)  
RADIO RECEIVER WITH TRAFFIC DECODER

Publication  
**EP 0123154 B1 19870624 (DE)**

Application  
**EP 84103252 A 19840323**

Priority  
DE 3310792 A 19830324

Abstract (en)  
[origin: EP0123154A1] 1. Radio receiver having an end stage (15) which energizes a loudspeaker (34) and/or head set, with the end stage being preceded by an audio frequency changeover switch (12) controlled frequency changeover switch (12) controlled by a control circuit (3) and having at least two switch positions (I, II) ; wherein a first r.f. reception/a.f. stage (13) containing a traffic decoder which can be tuned, at least to all traffic information radio transmitters, and a second r.f. reception/a.f. stage (14) independent from the first r.f. reception/a.f. stage and tunable in the VHF band, short wave band, medium wave band and/or long wave band, are connected to the audio frequency changeover switch (12) ; and wherein the audio frequency changeover switch (12) is normally located in the second switch position (II) which connects the second r.f. reception/a.f. stage (14) with the end stage, and only passes, with the aid of the control circuit (33), into the first switching position (I), in which it connects the first r.f. reception/a.f. stage to the end stage, during the presence of a switching signal at the output of the traffic information radio decoder (11) of the first r.f. reception/a.f. stage (13), characterized in that the audio frequency changeover switch (12) has a third switch position (III) in which a tape recorder (16) is connected to the end stage ; in that the second r.f. reception/a.f. stage (14) can be tuned to all traffic information radio transmitters and contains a traffic information radio decoder (11') ; in that the outputs of both traffic information radio decoders (11, 11') are applied to the control circuit (33) of the audio frequency changeover switch (12) via a priority circuit (18) which gives priority to the switching signal from the traffic information radio decoder (11) of the first r.f. reception/a.f. stage (13) in such a way that the audio frequency changeover switch (12) adopts the first switch position (I) when both traffic information radio decoders (11, 11') transmit a switching signal ; and in that the audio frequency changeover switch (12) adopts the third switching position (III) when the sound tape switch (17) is switched-on and no switching signal is present from one of the traffic information radio decoders (11, 11').

IPC 1-7  
**G08G 1/09**

IPC 8 full level  
**G08G 1/09** (2006.01)

CPC (source: EP)  
**G08G 1/094** (2013.01)

Cited by  
EP0333194A3

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI NL

DOCDB simple family (publication)  
**EP 0123154 A1 19841031; EP 0123154 B1 19870624**; AT E28009 T1 19870715; DE 3310792 A1 19841004; DE 3310792 C2 19860703; DE 3464425 D1 19870730

DOCDB simple family (application)  
**EP 84103252 A 19840323**; AT 84103252 T 19840323; DE 3310792 A 19830324; DE 3464425 T 19840323