

Title (en)  
CHILD-RESISTANT CLOSURE

Publication  
**EP 0123810 B1 19870923 (DE)**

Application  
**EP 84101911 A 19840223**

Priority  
DE 3315548 A 19830429

Abstract (en)  
[origin: US4624377A] A child resistant closure for bottles is provided that permit closure withdrawal by exerting an axial force and a simultaneous rotating movement. For this purpose, a clutch is provided between an inner cap and an outer cap of the closure with at least one elastic flexible clutch element which is ineffective in its rest position and which is deformable upon application of an axial downward force. In this manner, a sufficient friction lock is generated between the two caps, so that the outer cap takes along the inner cap during screwing on and unscrewing off. In the absence of the axial force the outer cap will slide over and not turn the inner cap.

IPC 1-7  
**B65D 55/02**

IPC 8 full level  
**B65D 39/08** (2006.01); **B65D 41/04** (2006.01); **B65D 50/04** (2006.01); **B65D 55/02** (2006.01)

CPC (source: EP US)  
**B65D 50/041** (2013.01 - EP US)

Cited by  
EP2028123A1; EP0490775A1; FR2670464A1; EP1803656A1; EP1002737A1

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0123810 A1 19841107; EP 0123810 B1 19870923**; AT E29860 T1 19871015; CA 1286254 C 19910716; DE 3315548 A1 19841206; DE 3466374 D1 19871029; DK 116384 A 19841030; DK 116384 D0 19840228; DK 158834 B 19900723; DK 158834 C 19901231; JP S6045158 A 19850311; NO 161170 B 19890403; NO 161170 C 19890712; NO 841675 L 19841030; US 4624377 A 19861125

DOCDB simple family (application)  
**EP 84101911 A 19840223**; AT 84101911 T 19840223; CA 452856 A 19840426; DE 3315548 A 19830429; DE 3466374 T 19840223; DK 116384 A 19840228; JP 8764584 A 19840427; NO 841675 A 19840427; US 79776285 A 19851113