

Title (en)  
Impulse generator.

Title (de)  
Impulsgenerator.

Title (fr)  
Générateur d'impulsion.

Publication  
**EP 0127043 A2 19841205 (DE)**

Application  
**EP 84105415 A 19840512**

Priority  
DE 3319404 A 19830528

Abstract (en)  
[origin: ES8507742A1] An impulse generator includes two pairs of contacts and one indexing disk whose indexing notches are capable of moving a central resilient indexing element. The indexing element moves either toward the one or the other pair of contacts depending on the rotation of the indexing disk. Each pair of contacts is a separate contact spring assembly (15, 16 17, 18). The indexing disk is positioned above the contact springs (15, 16 17, 18). The indexing element is a spiral spring (10) clamped either at one or at both ends, and disposed in such a way that the centerline (14) thereof extends in relation to the indexing notches (12' and 12) so that the latter deflects the spiral spring (10) laterally toward the contact springs (15, 16 17, 18). The spiral spring (10) is laterally deflected to actuate the respective inner contact spring (16, 17) of a contact spring assembly (15, 16 17, 18). This results in reduced abrasive by wear of the indexing disk, and insures that a good electrical contact is reliably made.

Abstract (de)  
Bei einem Impulsgenerator mit zwei Kontaktpaaren und einer Rastscheibe, deren Rastnocken ein mittleres federn-des Rastelement je nach Drehrichtung zum einen oder anderen Kontaktpaar hin bewegen kann, wird erfindungsgemäß für jedes Kontaktpaar ein getrennter Kontaktfedersatz (15, 16; 17, 18) vorgesehen, die Rastscheibe ist unterhalb oder oberhalb der Kontaktfedern (15, 16, 17, 18) angeordnet und das Rastelement ist als ein- oder beidseitig eingespannte Spiralfeder (10) ausgebildet und derart angeordnet, daß die Mittellinie (14) derselben senkrecht zur Richtung der Rastnocken (12) verläuft und diese die Spiralfeder (10) sowohl seitlich zu den Kontaktfedern (15, 16; 17, 18) als auch in Richtung der Rastnocken (12) auslenken kann und die Spiralfeder (10) je nach seitlicher Auslenkung die jeweils innere Kontaktfeder (16, 17) eines Kontaktfedersatzes (15, 16; 17, 18) betätigen kann. Hierdurch soll ein geringer Abrieb der Rastscheibe, eine gute Kontaktgabe und eine einwandfreie Rastung gewährleistet werden.

IPC 1-7  
**H01H 19/00**

IPC 8 full level  
**H03K 3/02** (2006.01); **H01H 1/26** (2006.01); **H01H 19/00** (2006.01); **H01H 19/56** (2006.01)

CPC (source: EP US)  
**H01H 19/005** (2013.01 - EP US); **H01H 19/56** (2013.01 - EP US); **H01H 2019/006** (2013.01 - EP US)

Cited by  
EP0229306A3

Designated contracting state (EPC)  
AT DE FR GB IT

DOCDB simple family (publication)  
**EP 0127043 A2 19841205; EP 0127043 A3 19870826; EP 0127043 B1 19901122**; AT E58612 T1 19901215; CA 1244071 A 19881101; DE 3319404 A1 19841129; DE 3319404 C2 19860123; DE 3483627 D1 19910103; ES 532770 A0 19850601; ES 8507742 A1 19850601; JP H0354896 B2 19910821; JP S6018014 A 19850130; US 4594483 A 19860610

DOCDB simple family (application)  
**EP 84105415 A 19840512**; AT 84105415 T 19840512; CA 455100 A 19840525; DE 3319404 A 19830528; DE 3483627 T 19840512; ES 532770 A 19840524; JP 10668284 A 19840528; US 61130484 A 19840517