

Title (en)
KEY

Publication
EP 0127113 B1 19900411 (DE)

Application
EP 84105827 A 19840522

Priority
• DE 3318886 A 19830525
• DE 3407033 A 19840227

Abstract (en)
[origin: US4631943A] A locking key, designed to preserve an indication of the lock-shifting (opening or closing) operation last performed, has a shank with an extension shaft rotatably received in an adjoining head, the relative rotation of the shank and the head being limited to 90 DEG or 180 DEG by a retaining pin in the head coacting with a part-circular recess on the shaft. The pin and the recess also serve to hold the head in a fixed axial position with reference to the shank. A spring-loaded detent in the shaft or elsewhere inside the head serves to index the two key portions in either of their limiting relative positions.

IPC 1-7
E05B 19/22

IPC 8 full level
E05B 19/22 (2006.01)

CPC (source: EP US)
E05B 19/22 (2013.01 - EP US); **Y10T 70/7802** (2015.04 - EP US); **Y10T 70/7876** (2015.04 - EP US); **Y10T 70/8027** (2015.04 - EP US)

Cited by
DE19606741C1; FR2760773A1; GB2355042A; GB2355042B; US5870917A; EP0838566A3; WO9706328A1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0127113 A2 19841205; **EP 0127113 A3 19850619**; **EP 0127113 B1 19900411**; DE 3407033 A1 19841129; DE 3481928 D1 19900517;
US 4631943 A 19861230

DOCDB simple family (application)
EP 84105827 A 19840522; DE 3407033 A 19840227; DE 3481928 T 19840522; US 61443684 A 19840525