

Title (en)

Method and apparatus for digitizing the maximum amplitude and time occurrence of an acoustic signal.

Title (de)

Verfahren und Anordnung zur Digitalisierung der Höchstamplitude und der Ankunftszeit eines akustischen Signals.

Title (fr)

Procédé et dispositif pour digitaliser l'amplitude maximale et le temps d'arrivée d'un signal acoustique.

Publication

EP 0129953 A2 19850102 (EN)

Application

EP 84302033 A 19840327

Priority

US 50736983 A 19830624

Abstract (en)

Digitizing and transmitting the maximum amplitude and time of occurrence of an analog signal is proposed for borehole televiewing apparatus to reduce the amount of data transmitted from a borehole tool to surface imaging equipment. During at least one established time window, the analog signal is amplitude sampled with an analog-to-digital converter 11. Each sample value is fed to a comparator 15 and compared with a previously stored maximum amplitude sample value and, if the present sample is greater than stored, it is stored as the new maximum amplitude sample value. Whenever a new maximum amplitude sample value is stored, its time of occurrence is also stored. At the end of each time window digital data representing the maximum amplitude and its time of occurrence are available for transmission so as to allow reconstruction of the original analog signal.

IPC 1-7

E21B 47/12; G01V 1/40

IPC 8 full level

E21B 47/14 (2006.01)

CPC (source: EP)

E21B 47/14 (2013.01)

Designated contracting state (EPC)

DE FR GB NL

DOCDB simple family (publication)

EP 0129953 A2 19850102; **EP 0129953 A3 19860625**; CA 1251866 A 19890328; NO 841650 L 19841227

DOCDB simple family (application)

EP 84302033 A 19840327; CA 451190 A 19840403; NO 841650 A 19840426