

Title (en)

Transmit-receive device for a presence-detecting radar, and method of making it.

Title (de)

Sende-Empfangseinrichtung für ein Radar zur Anwesenheitswahrnehmung und Verfahren zur Herstellung.

Title (fr)

Dispositif d'émission-réception pour radar de détection de présence, et procédé pour le réaliser.

Publication

EP 0131328 A1 19850116 (FR)

Application

EP 84200939 A 19840629

Priority

FR 8311005 A 19830701

Abstract (en)

1. A radar transmission-receiving arrangement, comprising a so-called "Doppler" module, having an aperture through which the actual transmission and reception are effected, a partially reflecting dielectric sheet and a dielectric lens which is positioned at a predetermined distance from the dielectric sheet by mechanical means being placed in front of the aperture of the module, characterized in that the partially reflecting sheet and said mechanical means are constituted by a foam block, which has a first plane face arranged in front of the aperture of the "Doppler" module and a second plane face parallel to the first face, against which the dielectric lens is placed.

Abstract (fr)

Dans un mini radar de détection de présence une plaque partiellement réfléchissante est placée devant l'orifice d'un dispositif émetteur-récepteur (1) et, en avant de cette plaque est disposée une lentille (7) qui est destinée à accroître la directivité du système. Un bloc de mousse (9) rigide assure à lui seul la fonction de plaque semi-réfléchissante (5) et la tenue mécanique de la lentille.

IPC 1-7

H01Q 19/08; H01Q 19/185

IPC 8 full level

H01Q 15/02 (2006.01); **G01S 7/02** (2006.01); **G01S 7/03** (2006.01); **H01Q 19/08** (2006.01); **H01Q 19/185** (2006.01)

CPC (source: EP)

H01Q 19/08 (2013.01); **H01Q 19/185** (2013.01)

Citation (search report)

- [A] FR 1514663 A 19680223 - SELENIA IND ELETTRONICHE
- [A] US 3389394 A 19680618 - LEWIS BERNARD L
- [A] US 3611392 A 197111005 - KNOX DENNIS MURDOCH
- [A] US 3414903 A 19681203 - BARTLETT HOMER E, et al
- PATENT ABSTRACTS OF JAPAN, vol. 3, no. 26, 6 mars 1979, page 15 E95; & JP-A-54 004 049 (NIPPON DENSIN DENWA KOSHA) 12-01-1979
- IEEE TRANSACTIONS ON MICROWAVE THEORY AND TECHNIQUES, vol. MTT-27, no. 9, septembre 1979, pages 797-799, IEEE, New York, US; P.S. NEELAKANTASWAMY et al.: "Dielectric hemisphere-loaded scalar horn as a Gaussian-beam launcher for microwave exposure studies"
- ARCHIV FÜR ELEKTRONIK UND ÜBERTRAGUNGSTECHNIK, vol. 31, no. 4, 1977, pages 173-175, Stuttgart, DE; P.S. NEELAKANTASWAMY et al.: "Near-field characteristics of a scalar horn-fed dielectric spherical radiator"

Cited by

EP0310414A3; EP0280379A3; EP0527569A1; WO9013927A1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0131328 A1 19850116; EP 0131328 B1 19880601; DE 3471840 D1 19880707; FR 2548466 A1 19850104; FR 2548466 B1 19851025; JP S6025304 A 19850208

DOCDB simple family (application)

EP 84200939 A 19840629; DE 3471840 T 19840629; FR 8311005 A 19830701; JP 13211184 A 19840628